

Start eco Surface Wall Adjustable Up & Down IP54
START eco Surface Wall Adjustable Up & Down IP54 2x150lm 830 BLK
0047910



Product features

- Exterior adjustable surface wall up and down light luminaire, black aluminium - RAL9005, 290lm, 5W, 58lm/W, 3000K, Driver Current: 700mA, CRI:80+, 220-240V, IP54, IK05, 30.000 hrs (L70), (HxWxD) 108x108x109mm, Class 1, energy class: A++, A+, A




PRODUCT OVERVIEW

Product name	START eco Surface Wall Adjustable Up & Down IP54 2x150lm 830 BLK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Wall surface mounted
Environment	External
General application	Residential & Consumer
ETIM Class	EC002892
E-number FI	4579447
Warranty	3 years
Fixture luminous flux (lm)	2x150
Luminaire efficacy (lm/W)	58
LOR (%)	100
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	94
Photobiological Risk Group	RG1
Total power consumption (W)	5
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL 9005 - Jet black
IP rating	IP54
IK rating	IK05
Product EAN number	5410288479101

PHOTOMETRY

Start eco Surface Wall Adjustable Up & Down IP54
START eco Surface Wall Adjustable Up & Down IP54 2x150lm 830 BLK
0047910



TECHNICAL DRAWINGS

