

RANA Linear Surface&Suspended - Opal Diffuser

RANA LINEAR S 3KLM WW OPAL 1-10
0051280



Product features

- Surface or Suspended LED Linear luminaire with Opal diffuser, Dimensions: 1150mm x 87mm x 87mm, Direct, White Body, 1-10V Dimmable, Warm White LED (3000K), 3220lm, 31W, 104lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse), Low LED Flicker (+/-5%), UGR<23, L90B10 at 50,000 hours, Electric Class1, Glow Wire Test 850°C




PRODUCT OVERVIEW

Product name	RANA LINEAR S 3KLM WW OPAL 1-10
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Fixture rating	Enclosed
Environment	Internal
General application	Office, Hospitality, Retail, Education
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	3220
Luminaire efficacy (lm/W)	103.87
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Glare control	< 23
Photobiological Risk Group	RG0
Total power consumption (W)	31
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Dimming method	1-10V (Analogue)
Minimum dimming level (%)	10
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK01
Product EAN number	5410288512808

RANA Linear Surface & Suspended - Opal Diffuser

RANA LINEAR S 3KLM WW OPAL 1-10
0051280

PHOTOMETRY



TECHNICAL DRAWINGS

