


START Downlight Flat IP44 Dimmable 108MM Round Recessed

Start Downlight Flat 108 IP44 600LM 840 DIM
0054119



Product features

- START Downlight Flat IP44 DIM is an integrated LED recessed downlight with a separate phase dimmable driver and Loop in out box; 7W; 600Lm; 86Lm/W; 4000K; IP44 rated from the front




PRODUCT OVERVIEW

Product name	Start Downlight Flat 108 IP44 600LM 840 DIM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278491
Warranty	5 years
Fixture luminous flux (lm)	600
Luminaire efficacy (lm/W)	85
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	7
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK06
Product EAN number	5410288541198

PHOTOMETRY

START Downlight Flat IP44 Dimmable 108MM Round Recessed

Start Downlight Flat 108 IP44 600LM 840 DIM
0054119



TECHNICAL DRAWINGS

