

RANA Linear Recessed - Opal Diffuser
RANA LINEAR R 3KLM NW OPAL D EMPRO
0052373



Product features

- Ceiling recessed LED Linear luminaire with Opal diffuser, Dimensions: 1154mm x 90mm x 91mm, Direct, White Body, DALI Dimmable (Switch-Dim), Emergency 3 hours maintained, Neutral White LED (4000K), 3210lm, 35W, 92lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse), Low LED Flicker (+/-5%), UGR<23, L90B10 at 50,000 hours, Electric Class1, Glow Wire Test 850°C, Can be covered with building insulation of Glass wool type




PRODUCT OVERVIEW

Product name	RANA LINEAR R 3KLM NW OPAL D EMPRO
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Environment	Internal
General application	Office, Hospitality, Retail, Education
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	3210
Luminaire efficacy (lm/W)	91.71
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Glare control	< 23
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	452
Total power consumption (W)	35
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288523736

RANA Linear Recessed - Opal Diffuser
RANA LINEAR R 3KLM NW OPAL D EMPRO
0052373

PHOTOMETRY



TECHNICAL DRAWINGS

