

START Downlight Flat Dimmable 226mm Round Surface


START eco Downlight Flat 226 1750lm 840 DIM Surface

0053948



Product features

- START eco Downlight Flat DIM Surface is an integrated LED surface mounted downlight with a separate, phase dimmable driver and loop in- out box, 17W; 1750Lm; 103Lm/W; 4000K; IP20.




PRODUCT OVERVIEW

Product name	START eco Downlight Flat 226 1750lm 840 DIM Surface
Technology	LED
Housing	Aluminium
Mount	Ceiling surface mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278202
Warranty	3 years
Fixture luminous flux (lm)	1750
Luminaire efficacy (lm/W)	103
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	120
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	17
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK06
Product EAN number	5410288539485

PHOTOMETRY

START Downlight Flat Dimmable 226mm Round Surface
START eco Downlight Flat 226 1750lm 840 DIM Surface
0053948



TECHNICAL DRAWINGS

