

Optix Surface 1200 Direct Medium Output

OPTIX SURFACE 1200 2L LUMI HCL TW ALU DALI

2023830



Product features

- OPTIX SURFACE 1200 2L LUMI HCL TW ALU DALI is a surface mounted luminaire for office and education applications with Aluminised plastic extra low glare optics and RAL9016 colour fixture body. DALI DT8 controlled tunable white light engine. 2700-6200K Tunable White LED, chromaticity tolerance of 3-step MacAdam ellipse. For 2700K - Colour rendering index Ra >98; Melanopic Ratio MEER: 0.524; Fidelity Index R :97; Gamut Index R :101. For 4000K - Colour rendering index Ra >95; Melanopic Ratio MEER: 0.819; Fidelity Index R :94; Gamut Index R :101. For 6200K - Colour rendering index Ra >98; Melanopic Ratio MEER: 1.071; Fidelity Index R :95; Gamut Index R :99. For 4000K luminous flux: 3500lm. Power consumption: 36W. Luminaire efficacy: 97lm/W. UGR<16 Luminance at 65°<200 Cd/m2, IK07, IP20. Photobiological safety risk group 0. Electrical protection Class I. Glow wire test 850°C. 68,000hrs L80B20 lifespan.




PRODUCT OVERVIEW

Product name	OPTIX SURFACE 1200 2L LUMI HCL TW ALU DALI
Technology	LED LumiNature
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
Fixture rating	Enclosed
General application	Education, Office
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	3500
Luminaire efficacy (lm/W)	97
Colour temperature (K)	4000
Light colour	Tuneable White HCL
CRI (Ra)	95
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 16
Photobiological Risk Group	RG0
Total power consumption (W)	36
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238309

Optix Surface 1200 Direct Medium Output
OPTIX SURFACE 1200 2L LUMI HCL TW ALU DALI
2023830

PHOTOMETRY



TECHNICAL DRAWINGS

