


# Colossal 600 Prismatic

COLOSSAL 600mm 840 PRISM DIR+HAL WHITE DALI  
2071217



## Product features

- 600mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with PMMA prismatic diffuser. Direct/indirect (halo) light distribution, 4090lm luminous flux, 31.3W system power, 131lm/W luminaire efficacy. DALI dimmable. Colour rendering index Ra >80, 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40, IK03. 350mA drive current. UGR 19. Electrical protection Class1, 220-240V. Reported lifetime 66k hours L90B10.




## PRODUCT OVERVIEW

|                                 |                                             |
|---------------------------------|---------------------------------------------|
| Product name                    | COLOSSAL 600mm 840 PRISM DIR+HAL WHITE DALI |
| Technology                      | LED (3 SDCM)                                |
| Cap/Base                        | N/A                                         |
| Housing                         | Aluminium                                   |
| Mount                           | Suspended                                   |
| General application             | Hospitality, Office                         |
| ETIM Class                      | EC002892                                    |
| Warranty                        | 5 years                                     |
| Fixture luminous flux (lm)      | 4090                                        |
| Luminous flux (lm)              | 4090                                        |
| Luminaire efficacy (lm/W)       | 131                                         |
| Colour temperature (K)          | 4000                                        |
| Colour Code                     | 840                                         |
| Light colour                    | Neutral White                               |
| CRI (Ra)                        | 80                                          |
| Colour Variation Initial (SDCM) | SDCM3                                       |
| Glare control                   | < 19                                        |
| Photobiological Risk Group      | RG0                                         |
| Total power consumption (W)     | 31.3                                        |
| Electrical protection           | Class I                                     |
| Control gear type               | Other                                       |
| Dimmable                        | Yes                                         |
| Dimming method                  | DALI-2                                      |
| LED Flickering Rate             | Ultra low (5% or less)                      |
| Housing colour                  | RAL 9016 - Traffic white / Bezel            |
| IP rating                       | IP40/20                                     |
| IK rating                       | IK07                                        |
| Product EAN number              | 5025768712175                               |

## PHOTOMETRY

Colossal 600 Prismatic  
COLOSSAL 600mm 840 PRISM DIR+HAL WHITE DALI  
2071217



TECHNICAL DRAWINGS

