

Colossal 600 Prismatic


COLOSSAL 600mm 830 PRISM DIR WHITE DALI

2071169



Product features

- 600mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with PMMA prismatic diffuser. Direct light distribution, 3805lm luminous flux, 31.3W system power, 122lm/W luminaire efficacy. DALI dimmable. Colour rendering index Ra >80, 3000K Warm White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40, IK03. 350mA drive current. UGR 19. Electrical protection Class1, 220-240V. Reported lifetime 66k hours L90B10.




PRODUCT OVERVIEW

Product name	COLOSSAL 600mm 830 PRISM DIR WHITE DALI
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting, Suspended
General application	Hospitality, Office
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	3805
Luminous flux (lm)	3805
Luminaire efficacy (lm/W)	122
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	31.3
Electrical protection	Class I
Control gear type	Other
Dimmable	Yes
Dimming method	DALI-2
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK07
Product EAN number	5025768711697

PHOTOMETRY

Colossal 600 Prismatic
COLOSSAL 600mm 830 PRISM DIR WHITE DALI
2071169



TECHNICAL DRAWINGS

