

Sterling Bulkhead - LED
STERLING IP65 IK10 1477LM 840 SILVER
4063837



Product features

- Led exterior bulkhead, Unique feature allowing a choice between High Output or High Efficiency with the flick of a switch, die-cast aluminium body, 759/1477LM, 9/17W, 84/87LM/W, 4000K, Driver Current: 350/750mA, CRI80, Non dimmable, IP65, IK10, lifespan 100,000hrs (L70:B50), (HxWxD) 350 x 350 x 128mm, 3.4kg, 3 step MacAdam ellipse, RAL 9006, Class 1, 230V, energy class: A++, A+, A



PRODUCT OVERVIEW

Product name	STERLING IP65 IK10 1477LM 840 SILVER
Technology	LED
Environment	Indoor, Outdoor
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail
ETIM Class	EC002892
E-number FI	4579257
Warranty	5 years
Fixture luminous flux (lm)	759/1477
Luminaire efficacy (lm/W)	87
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Photobiological Risk Group	RG1
Total power consumption (W)	9/17
Electrical protection	Class I
Dimmable	No
Housing colour	Silver
IP rating	IP65
IK rating	IK10
Product EAN number	5026524638371

PHOTOMETRY

Sterling Bulkhead - LED

STERLING IP65 IK10 1477LM 840 SILVER
4063837

0.5	1.52	E(0°) E(C0)	96 80
1.0	3.04	E(0°) E(C0)	241 20
1.5	4.57	E(0°) E(C0)	167 9
2.0	6.09	E(0°) E(C0)	125 5
2.5	7.61	E(0°) E(C0)	99 5
3.0	9.13	E(0°) E(C0)	82 4



Distance [m] Cone diameter [m] Illuminance [lx]

C0 - C180 (Half beam angle: 113.4°)

0.5	1.55	E(0°) E(C0)	1820 150
1.0	3.10	E(0°) E(C0)	455 39
1.5	4.65	E(0°) E(C0)	303 17
2.0	6.21	E(0°) E(C0)	227 10
2.5	7.76	E(0°) E(C0)	181 6
3.0	9.31	E(0°) E(C0)	151 4

Distance [m] Cone diameter [m] Illuminance [lx]

C0 - C180 (Half beam angle: 114.4°)



TECHNICAL DRAWINGS

