


Raiden 8KLM

Raiden IP66 8KLM 840 Symmetric Wide DALI
2824088



Product features

- Outdoor and indoor floodlight range with in house design, comes complete with 1m flying lead and adjustable bracket, aluminium housing, RAL 9022 - Pearl light grey, clear glass diffuser, IP66, IK08, Class I, 4000K, DALI dimmable, 9100lm, 67W, 136lm/W, CRI80, Symmetric Wide beam angle 60°, 100000 hrs L90B50 lifespan, 327x270x74mm (LxWxH) dimensions, 4.3kg weight. Ball-impact-resistance according to DIN57710-13 VDE 0710 13/5.81, DIN 18032-3 only with the separate wire guard accessory fitted.




PRODUCT OVERVIEW

Product name	Raiden IP66 8KLM 840 Symmetric Wide DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
General application	Logistics & Industry
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	9100
Luminaire efficacy (lm/W)	136
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	60
Photobiological Risk Group	RG1
Total power consumption (W)	67
Electrical protection	Class I
Dimmable	Yes
Dimming method	DALI-2
Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Product EAN number	5025768240883

PHOTOMETRY

Raiden 8KLM
Raiden IP66 8KLM 840 Symmetric Wide DALI
2824088



TECHNICAL DRAWINGS

