## Raiden 8KLM

# Raiden IP66 8KLM 830 Asymmetric Wide DALI 2824034



#### **Product features**

Outdoor and indoor floodlight range with in house design, comes complete with 1m flying lead and adjustable bracket, aluminium housing, RAL 9022 - Pearl light grey, clear glass diffuser, IP66, IK08, Class I, 3000K, DALI dimmable, 8600lm, 67W, 128lm/W, CRI80, Asymmetric Wide beam angle 110\*50°, 100000 hrs L90B50 lifespan, 327x270x74mm (LxWxH) dimensions, 4.3kg weight. Ball-impact-resistance according to DIN57710-13 VDE 0710 13/5.81, DIN 18032-3 only with the separate wire guard accessory fitted.


























#### PRODUCT OVERVIEW

logy se	LED N/A
60	N1/A
3 <del>0</del>	IN/A
g	Aluminium
l application	Logistics & Industry
lass	EC001744
ty	5 years
luminous flux (lm)	8600
ire efficacy (Im/W)	128
temperature (K)	3000
olour	Warm White
a)	80
Variation Initial (SDCM)	SDCM3
Angle (°)	110*50
iological Risk Group	RG1
ower consumption (W)	67
al protection	Class I
ble	Yes
g method	DALI-2
g colour	RAL 9022 - Pearl light grey
g	IP66
g	IK08
t EAN number	5025768240340

#### **PHOTOMETRY**

Concord

# Raiden 8KLM Raiden IP66 8KLM 830 Asymmetric Wide DALI 2824034



### **TECHNICAL DRAWINGS**

