


Giotto LED 305
GIOTTO 305 4000K RECESSED 1-10V
3034766



Product features

- Ambient and decorative round, recessed mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 1750lm, 14.7W, 119lm/W, 4000K, CRI 80, 1-10V dimmable, 100,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.




PRODUCT OVERVIEW

Product name	GIOTTO 305 4000K RECESSED 1-10V
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Hospitality, Logistics & Industry
ETIM Class	EC002892
E-number FI	4270183
Warranty	5 years
Fixture luminous flux (lm)	1750
Luminous flux (lm)	1750
Luminaire efficacy (lm/W)	119
Colour temperature (K)	4000
Colour Code	840
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	19
Electrical protection	Class I
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	Yes
Dimming method	1-10V (Analogue)
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP44
IK rating	IK10
Product EAN number	8711971347668

Giotto LED 305
GIOTTO 305 4000K RECESSED 1-10V
3034766

PHOTOMETRY



TECHNICAL DRAWINGS

