

ToLEDo RT T25 V5 CL 250LM 827 E14 SL 0029541







Features

· Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps ToLEDo Retro T25 lamp is the ideal replacement for incandescent cooker hood lamps Same look, size and functionality as incandescent lamps Omni-directional light distribution Gives same sparkling light effect as incandescent lamp Dimensionally identical to incandescent lamps - fits all fixtures Environment friendly - no mercury and lower CO2 emissions

Product Overview

Technology Watt (Rated) (W) 2.5 Type LED exchangeable Cap/Base E14 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4740958 Luminous flux (Im) 250 Colour temperature (K) 2700 Light colour CRI (Ra) 80 Colour Variation Initial (SDCM) Photobiological Risk Group Wattage (W) Product Voltage (V) Dimmable LED 2.5 LED LED A. S. B. Colour wender A. Consumer E14 Hospitality, Residential & Consumer E2001959 E-001959 E-00	Product name	ToLEDo RT T25 V5 CL 250LM 827 E14 SL
Type LED exchangeable Cap/Base E14 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4740958 Luminous flux (Im) 250 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) 6 Photobiological Risk Group RG1 Wattage (W) 2.5 Product Voltage (V) 230	Technology	LED
Cap/Base E14 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4740958 Luminous flux (Im) 250 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) 6 Photobiological Risk Group RG1 Wattage (W) 230	Watt (Rated) (W)	2.5
Fixture rating General application Hospitality, Residential & Consumer ETIM Class E-number FI 4740958 Luminous flux (Im) 250 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) Photobiological Risk Group Wattage (W) Product Voltage (V) 290	Туре	LED exchangeable
General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4740958 Luminous flux (Im) 250 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) 6 Photobiological Risk Group RG1 Wattage (W) 2.5 Product Voltage (V) 230	Cap/Base	E14
ETIM Class E-number FI 4740958 Luminous flux (Im) 250 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) Photobiological Risk Group RG1 Wattage (W) Product Voltage (V) EC001959 EC001959 A740958 B0 Colour temperature (K) Ambient Spool	Fixture rating	Open
E-number FI Luminous flux (Im) 250 Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) Photobiological Risk Group RG1 Wattage (W) Product Voltage (V) 250 R4740958 R696 R696 R696 R696 R696 R696 R696 R69	General application	Hospitality, Residential & Consumer
Luminous flux (Im)250Colour temperature (K)2700Light colourHomelightCRI (Ra)80Colour Variation Initial (SDCM)6Photobiological Risk GroupRG1Wattage (W)2.5Product Voltage (V)230	ETIM Class	EC001959
Colour temperature (K) 2700 Light colour Homelight CRI (Ra) 80 Colour Variation Initial (SDCM) 6 Photobiological Risk Group RG1 Wattage (W) 2.5 Product Voltage (V) 230	E-number FI	4740958
Light colour CRI (Ra) 80 Colour Variation Initial (SDCM) Photobiological Risk Group RG1 Wattage (W) 2.5 Product Voltage (V) 230	Luminous flux (Im)	250
CRI (Ra) 80 Colour Variation Initial (SDCM) 6 Photobiological Risk Group RG1 Wattage (W) 2.5 Product Voltage (V) 230	Colour temperature (K)	2700
Colour Variation Initial (SDCM) 6 Photobiological Risk Group RG1 Wattage (W) 2.5 Product Voltage (V) 230	Light colour	Homelight
Photobiological Risk Group RG1 Wattage (W) 2.5 Product Voltage (V) 230	CRI (Ra)	80
Wattage (W) 2.5 Product Voltage (V) 230	Colour Variation Initial (SDCM)	6
Product Voltage (V) 230	Photobiological Risk Group	RG1
5 ()	Wattage (W)	2.5
Dimmable No	Product Voltage (V)	230
	Dimmable	No



ToLEDo RT T25 V5 CL 250LM 827 E14 SL **0029541**

Average life (Nominal) (h) 15000

Product EAN number 5410288295411

Warranty 3 years

Technical drawings

