

Concord

BEACON XXL NB HO 3K L3 WHT
2059308



Features

• 2059308 BEACON XXL NB HO 3K L3 WHT Integrated LED spotlight, white RAL 9016, compact and minimalist design, ideal for double height spaces, retail and display applications, die-cast aluminium body, passive cooling heatsink, beam angle: 21° narrow beam, optics: Fresnel lens for controlled beam, colour temperature: 3000K warm white, total system power: 48W, total fixture output: 4351lm, luminaire efficacy: 91lm/W, LOR: 100%, colour rendering: Ra 85 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 1200mA, electronic driver, non-dimmable, switched only, power factor: 0.98 electrical protection: CLASS I, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, lockable positioning using Allen key, dimen...


Product Overview

Product name	BEACON XXL NB HO 3K L3 WHT
Technology	LED
Housing	Aluminium
Mount	Track mounting
Environment	Internal
General application	Retail
ETIM Class	EC001744
E-number FI	4278855
E-number SE	7401091
Fixture luminous flux (lm)	4351
Luminaire efficacy (lm/W)	90.65
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White

BEACON XXL NB HO 3K L3 WHT 2059308

CRI (Ra)	85
Colour Consistency (SDCM)	3
Beam Angle (°)	21
Photobiological Risk Group	RG1
Total power consumption (W)	48
Product Voltage (V)	240
Electrical protection	Class I
Control gear type	Electronic ballast
Housing colour	White
IP rating	IP20
Product EAN number	5025768593088
Warranty	5 years
Dimming method	N/A

Photometry



Technical drawings

