

Inverto Pend Rmt WW 1-10v Silver 3080127



Features

- Pendant luminaire with remote driver, wire to base with pluggable connection for easy installation, suitable for looping, switchable driver, silver coloured aluminium housing, 1,566lm, 16W, 98lm/W, 3000K, 350mA , CRI:80, 40° beam Angle, 1-10V dimmable, IP20, IK07, lifespan: 60,000hrs (L80:B20), 18.50x29.6x11.5mm.

Product Overview

Product name	Inverto Pend Rmt WW 1-10v Silver
Technology	LED
Housing	Aluminium
Mount	Pendant surface
Environment	Internal
General application	Hospitality
ETIM Class	EC001743
Fixture luminous flux (lm)	1566
Luminaire efficacy (lm/W)	98
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Beam Angle (°)	40
Photobiological Risk Group	RG1
Total power consumption (W)	16
Electrical protection	Class II
Control gear type	Electronic ballast

Inverto Pend Rmt WW 1-10v Silver 3080127

Dimmable	Yes
Minimum dimming level (%)	5
Housing colour	RAL 9022 - Pearl light grey
IP rating	IP20
IK rating	IK07
Product EAN number	8711971801276
Warranty	5 years
Dimming method	1-10V (Analogue)

Technical drawings

