



Features

- 50,000 hours average rated lifetime Last 2.5 times longer than 49W 1449mm fluorescent tri-phosphor T5 lamp High switching cycles – 200,000X High lumen efficacy Omni-directional light distribution and wide beam angle Minimum and maximum operating temperature: -20°C to 50°C Glass construction and polycarbonate end-caps Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast Works only with compatible electronic ballasts Ideal for factories, parking lots, supermarkets, department stores, schools and offices

Product Overview

Product name	ToLEDo Superia T5 ECG HO V3 5FT 3900LM 840
Technology	LED
Watt (Rated) (W)	26
Lamp shape	Tube, double-ended
Type	LED exchangeable
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4940792
Luminous flux (lm)	3900
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Wattage (W)	26
Product Voltage (V)	110



ToLEDo Superia T5 ECG HO V3 5FT 3900LM 840
0029269

Dimmable	No
Average life (Nominal) (h)	50000
IP rating	IP20
Product EAN number	5410288292694
Warranty	5 years

Technical drawings

