

# REFLED R50 V3 470LM 865 E14 SL 0026335













#### **Features**

• • Energy efficient LED alternative for traditional incandescent and halogen blown reflector lamp. Modern construction and attractive design. Mercury free solution. Long average rated lifetime: 15,000 hours. Lower maintenance cost compared to traditional lamps• Non-dimmable• 3 years warranty• Perfect for general lighting applications: residential lighting, down lights, hotels, hotels, restaurants, bars, lobbies, corridors, halls, etc

#### **Product Overview**

Product name	REFLED R50 V3 470LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740800
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	6
Beam Angle (°)	120
Wattage (W)	5
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288263359
Warranty	3 years



# REFLED R50 V3 470LM 865 E14 SL **0026335**

# **Data table**

#### **GENERAL DATA**

Product name	REFLED R50 V3 470LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq	25
(°C)	
ETIM Class	EC001959
E-number FI	4740800
Warranty	3 years

#### **OPTICAL DATA**

Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	6
Luminous Intensity (cd)	136
Beam Angle (°)	120

# **ELECTRICAL DATA**

Wattage (W)	5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max)	2
(s)	
Mains voltage (V)	220-240V
Product Voltage (V)	230
Lamp power factor	0.5
Control gear required	No



# REFLED R50 V3 470LM 865 E14 SL **0026335**

No. Of switching cycles before premature failures	>50000
Dimmable	No
Nominal Frequency (Hz)	50/60Hz

# **LIFETIME DATA**

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

# **PHYSICAL DATA**

Nominal Product Length (mm)	83
Nominal Product Diameter (mm)	50
Weight (kg)	0.024

#### **PACKAGING**

Single packaging type	Carton
Product EAN number	5410288263359
Packaging single length / height (cm)	5.0
Packaging single width (cm)	5.0
Packaging single depth (cm)	7.8
DUN14 (outer)	15410288263356
Units per outer package	6
Packaging outer length / height (cm)	15.6
Packaging outer width (cm)	10.8
Packaging outer depth (cm)	8.8

# **SAFETY DATA**

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures