

F15W REPTISTAR UV-B 10%
0000741



Features

- Provides the necessary UVB radiation for reptile habitats. Daylight colour temperature 6500K. This lamp emits UV-radiation, Avoid exposure.

Product Overview

Product name	F15W REPTISTAR UV-B 10%
Technology	Fluorescent
Lamp shape	Tubular shape
Type	T8
Cap/Base	G13
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	SPG
ETIM Class	EC002962
Luminous flux (lm)	300
Colour temperature (K)	6500
Light colour	UV
Wattage (W)	15.00
Product Voltage (V)	55
Dimmable	Yes
Average life (Nominal) (h)	14000
Product EAN number	5410288007410
Dimming method	Mains: leading / trailing edge

Data table

F15W REPTISTAR UV-B 10% 0000741

GENERAL DATA

Product name	F15W REPTISTAR UV-B 10%
Technology	Fluorescent
Lamp shape	Tubular shape
Type	T8
Cap/Base	G13
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	SPG
Operating temperature range (°C)	-15°C...+40°C
ETIM Class	EC002962

OPTICAL DATA

Luminous flux (lm)	300
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	6500
Light colour	UV
Adjustable chromaticity	N

ELECTRICAL DATA

Wattage (W)	15.00
Watt (Rated) - High frequency (W)	13.50
Current (A)	0.310
Product Voltage (V)	55
Control gear required	Yes
Transformer required	No
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Drive current (mA)	310

LIFETIME DATA

Average life (Nominal) (h)	14000
----------------------------	-------

F15W REPTISTAR UV-B 10% 0000741

PHYSICAL DATA

Nominal Product Length (mm)	450.0
Nominal Product Diameter (mm)	26
Max. Length base to base (mm) - A	437.4
Length base to pin Min-Max (mm) - B	442.1-444.5
Max. Lamp Length (mm) - C/L	451.6
Max. Lamp Diameter (mm) - D	28.0
Weight (kg)	0.062

PACKAGING

Single packaging type	Carton
Product EAN number	5410288007410
Packaging single length / height (cm)	67.1
Packaging single width (cm)	2.7
Packaging single depth (cm)	2.7
DUN14 (outer)	15410288007417
Units per outer package	10
Packaging outer length / height (cm)	70.1
Packaging outer width (cm)	6.5
Packaging outer depth (cm)	14.7

SAFETY DATA

Lamp mercury content (mg)	2.80
Optimal operating condition (°C)	-15-40
Breakage cleaning instructions	Applicable
Special purpose lamp	Yes
Intended purpose	High UV Content (>2mW/klm)(Terrarium High UV lamps)
Dry applications use only	No
Suitable for household illumination	No
Safety message	Not suitable for household