



Features

- 50,000 hours average rated lifetime (L70 F50)Last 2.5 times longer than 49W 1449mm fluorescent tri-phosphor T5 lampHigh switching cycles - 200,000X High lumen efficacy - 154lm/WOmni-directional light distribution and wide beam angleMinimum and maximum operating temperature: -20°C to 50°CGlass construction and polycarbonate end-capsOnly suitable for direct mains (AC 220-240V) operationIdeal for factories, parking lots, supermarkets, department stores, schools and officesNot suitable for operation with electronic/ECG or magnetic/CCG ballasts

Product Overview

Product name	ToLEDo SUPERIA T5 AC 5FT 4000LM 840
Technology	LED
Watt (Rated) (W)	26
Cap/Base	G5
General application	Office, Hospitality, Logistics & Industry, Retail, Residential & Consumer, Museums & Galleries, Education
ETIM Class	EC001959
E-number FI	4740765
Luminous flux (lm)	4000
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Wattage (W)	26
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	50000
Product EAN number	5410288280400
Warranty	5 years

ToLEDo SUPERIA T5 AC 5FT 4000LM 840 0028040

Data table

GENERAL DATA

Product name	ToLEDo SUPERIA T5 AC 5FT 4000LM 840
Technology	LED
Watt (Rated) (W)	26
Cap/Base	G5
General application	Office, Hospitality, Logistics & Industry, Retail, Residential & Consumer, Museums & Galleries, Education
ETIM Class	EC001959
E-number FI	4740765
Warranty	5 years

OPTICAL DATA

Luminous flux (lm)	4000
Luminous flux (Rated) (lm)	4000
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Wattage (W)	26
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<2
Product Voltage (V)	230
Lamp power factor	0.9
Control gear required	No
No. Of switching cycles before premature failures	>200000

ToLEDo SUPERIA T5 AC 5FT 4000LM 840 0028040

Dimmable	No
----------	----

LIFETIME DATA

Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

PHYSICAL DATA

Weight (kg)	0.174
-------------	-------

PACKAGING

Single packaging type	Carton
Product EAN number	5410288280400
Packaging single length / height (cm)	146.2
Packaging single width (cm)	1.8
Packaging single depth (cm)	1.8
DUN14 (outer)	15410288280407
Units per outer package	10
Packaging outer length / height (cm)	152.5
Packaging outer width (cm)	15.6
Packaging outer depth (cm)	8.0

SAFETY DATA

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture