



Features

- Premium performance professional LED GU10 range with the same look and feel of traditional halogen GU10 lamp Recreates backlight effect similar to halogen dichroic lamps Full glass design - means no colours clashing between lamp and fixture Very long lifetime of up to 25,000 hours COOLFIT functionality – ensures overheat and over temperature protection High switching cycles: >100,000 High colour rendering: CRI80 Dimmable with approved dimmers Warranty: 5 Years


Product Overview

Product name	RefLED Superia Retro ES50 V3 475LM DIM 865 36 SL
Technology	LED
Watt (Rated) (W)	5
Type	LED exchangeable
Fixture rating	Open
General application	Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4741028
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	6
Beam Angle (°)	36
Photobiological Risk Group	RG1
Wattage (W)	5

RefLED Superia Retro ES50 V3 475LM DIM 865 36 SL
0029136

Product Voltage (V)	230
Dimmable	Yes
Average life (Nominal) (h)	25000
Product EAN number	5410288291369
Warranty	5 years

Technical drawings



Data table

GENERAL DATA

Product name	RefLED Superia Retro ES50 V3 475LM DIM 865 36 SL
Technology	LED
Watt (Rated) (W)	5
Type	LED exchangeable
Fixture rating	Open
General application	Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail
Operating temperature range (°C)	-20°C...+50°C

RefLED Superia Retro ES50 V3 475LM DIM 865 36 SL 0029136

Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4741028
Warranty	5 years

OPTICAL DATA

Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	6
Luminous Intensity (cd)	860
Beam Angle (°)	36
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Wattage (W)	5
Equivalent watt (W)	60
Product Voltage (V)	230
Control gear required	No
No. Of switching cycles before premature failures	>100000
Transformer required	No
Dimmable	Yes
Inrush Current (A)	0.46
Inrush Duration (µs)	28
Lamp Energy Label (class)	E
Max. Luminaires per 16A C Breaker	667
Max. Luminaires per 16A B Breaker	667

LIFETIME DATA

RefLED Superia Retro ES50 V3 475LM DIM 865 36 SL 0029136

Lifespan L70 B50	25000
Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

PHYSICAL DATA

Nominal Product Height (mm)	54
Nominal Product Diameter (mm)	50
Weight (kg)	0.05

PACKAGING


Single packaging type	Carton
Product EAN number	5410288291369
Packaging single length / height (cm)	8.2
Packaging single width (cm)	6.1
Packaging single depth (cm)	5.1
DUN14 (inner)	25410288291363
Units per inner package	6
Packaging inner length / height (cm)	9.2
Packaging inner width (cm)	16.4
Packaging inner depth (cm)	13.1
DUN14 (outer)	15410288291366
Units per outer package	60
Packaging outer length / height (cm)	20.8
Packaging outer width (cm)	17.8
Packaging outer depth (cm)	68.5

SAFETY DATA

Optimal operating condition (°C)	-20-50
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Dimmable with approved dimmers

Energy label

**ENERG**
SYLVANIA
0029136




5
kWh/1000h



2019/2015

**ENERG**
SYLVANIA
0029136



5
kWh/1000h



2019/2015