



Features

- LED Striplight replacement for incandescent lamp
High lumen output: up to 806lm 15,000 hours average rated life Up to 85% energy saving Creates a warm ambiance similar to traditional lamps Perfect for kitchen, mirror lighting, shaver lighting, bathroom 3 year warranty



Product Overview

Product name	ToLEDo Striplight V3 300MM 450LM S14s
Technology	LED
Watt (Rated) (W)	5
Type	LED exchangeable
Cap/Base	S14s
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4741150
Luminous flux (lm)	450
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0
Wattage (W)	5
Product Voltage (V)	230
Dimmable	No

ToLEDo Striplight V3 300MM 450LM S14s 0028105

Average life (Nominal) (h)	15000
Product EAN number	5410288281056
Warranty	3 years

Technical drawings



Data table

GENERAL DATA

Product name	ToLEDo Striplight V3 300MM 450LM S14s
Technology	LED
Watt (Rated) (W)	5
Type	LED exchangeable
Cap/Base	S14s
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C

ToLEDo Striplight V3 300MM 450LM S14s 0028105

Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4741150
Warranty	3 years

OPTICAL DATA

Luminous flux (lm)	450
Luminous flux (Rated) (lm)	450
Colour temperature (K)	2700
Correlated colour temperature range (K)	2430 - 2970
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Wattage (W)	5
Equivalent watt (W)	35
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	1
Control gear required	No
No. Of switching cycles before premature failures	>100000
Transformer required	No
Dimmable	No
Inrush Current (A)	2.4
Inrush Duration (µs)	200
Lamp Energy Label (class)	F

ToLEDo Striplight V3 300MM 450LM S14s 0028105

Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	460
Max. Luminaires per 13A C Breaker	598
Max. Luminaires per 16A C Breaker	67
Max. Luminaires per 20A C Breaker	920
Max. Luminaires per 16A B Breaker	33

LIFETIME DATA

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

PHYSICAL DATA

Nominal Product Length (mm)	298
Nominal Product Diameter (mm)	48
Weight (kg)	0.08

PACKAGING

Single packaging type	Carton
Product EAN number	5410288281056
Packaging single length / height (cm)	30.7
Packaging single width (cm)	5.0
Packaging single depth (cm)	3.0
DUN14 (outer)	15410288281053
Units per outer package	6
Packaging outer length / height (cm)	31.3
Packaging outer width (cm)	10.6
Packaging outer depth (cm)	10.1

SAFETY DATA

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No

SYLVANIA


ToLEDo Striplight V3 300MM 450LM S14s
0028105

Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

Energy label



0028105




5
kWh/1000h



2019/2015



0028105



5
kWh/1000h



2019/2015