



Features


- Perfect for decorative and general lighting applications and creates a warm ambience similar to traditional lamps
- The versatile ToLEDo Retro candle range is the ideal replacement for halogen and incandescent lamps and perfect for chandeliers and decorative applications
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- A++ energy rating
- Gives same sparkling light effect as the incandescent lamp
- Dimensionally identical to incandescent lamps - fits all fixtures
- Environment-friendly - no mercury and lower CO2 emissions

Product Overview

Product name	ToLEDo RT CANDLE TW V4 CL 250LM 827 E14 SL
Technology	LED
Watt (Rated) (W)	2.5
Type	ToLEDo Retro Candle
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740641
Luminous flux (lm)	250
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	300
Wattage (W)	2.5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288273365
Warranty	3 years

ToLEDo RT CANDLE TW V4 CL 250LM 827 E14 SL
0027336

Technical drawings



Data table

GENERAL DATA

Product name	ToLEDo RT CANDLE TW V4 CL 250LM 827 E14 SL
Technology	LED
Watt (Rated) (W)	2.5
Type	ToLEDo Retro Candle
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740641
Warranty	3 years

OPTICAL DATA

Luminous flux (lm)	250
Luminous flux (Rated) (lm)	250

ToLED_o RT CANDLE TW V4 CL 250LM 827 E14 SL 0027336

Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	300
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Wattage (W)	2.5
Equivalent watt (W)	25
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
Control gear required	No
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	1.2
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	83
Max. Luminaires per 16A C Breaker	133
Max. Luminaires per 20A C Breaker	167

LIFETIME DATA

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

PHYSICAL DATA

Nominal Product Length (mm)	97
Nominal Product Diameter (mm)	35
Weight (kg)	0.016

PACKAGING

ToLEDo RT CANDLE TW V4 CL 250LM 827 E14 SL 0027336

Single packaging type	Carton
Product EAN number	5410288273365
Packaging single length / height (cm)	10.6
Packaging single width (cm)	3.8
Packaging single depth (cm)	3.8
DUN14 (inner)	25410288273369
Units per inner package	6
Packaging inner length / height (cm)	15.0
Packaging inner width (cm)	11.1
Packaging inner depth (cm)	12.9
DUN14 (outer)	15410288273362
Units per outer package	60
Packaging outer length / height (cm)	56.9
Packaging outer width (cm)	31.9
Packaging outer depth (cm)	15.3

SAFETY DATA

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures