



Features

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps
- Omni-directional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes
- Lumen output - 1800lm
- High lumen efficacy - 103 lm/W
- Switching cycles - 100,000X
- Average rated life 25,000 hours
- Lamp length - 1200mm
- Wide beam angle
- Suitable for general illumination in offices, supermarkets, department stores, parking lots
- Suitable for operation with electromagnetic gears/CCG and direct mains operation (220-240V)
- 2-Year warranty



Product Overview

Product name	ToLEDo T8 V4 4FT 1800LM 865 25K
Technology	LED
Watt (Rated) (W)	17.5
Lamp shape	Tube, double-ended
Type	LED exchangeable
Cap/Base	G13
Lamp finish	Opal
Fixture rating	Open
General application	Education, Logistics & Industry, Office, Residential & Consumer
ETIM Class	EC001959
E-number FI	4941322
Luminous flux (lm)	1800
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	180
Photobiological Risk Group	RG0

ToLEDo T8 V4 4FT 1800LM 865 25K
0029303

Wattage (W)	17.5
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	25000
IP rating	IP20
Product EAN number	5410288293035
Warranty	2 years

Technical drawings



Data table

GENERAL DATA

Product name	ToLEDo T8 V4 4FT 1800LM 865 25K
Technology	LED
Watt (Rated) (W)	17.5
Lamp shape	Tube, double-ended
Type	LED exchangeable
Cap/Base	G13
Lamp finish	Opal
Fixture rating	Open

ToLEDo T8 V4 4FT 1800LM 865 25K 0029303

General application	Education, Logistics & Industry, Office, Residential & Consumer
Operating temperature range (°C)	-20°C...+45°C
Performance ambient temperature Tq (°C)	55
ETIM Class	EC001959
E-number FI	4941322
Warranty	2 years

OPTICAL DATA

Luminous flux (lm)	1800
Luminous flux (Rated) (lm)	1800
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	180
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Wattage (W)	17.5
Product Voltage (V)	230
Lamp power factor	0.5
Control gear required	No
No. Of switching cycles before premature failures	>50000
Transformer required	No
Dimmable	No
Inrush Current (A)	8.0
Inrush Duration (µs)	420
Lamp Energy Label (class)	F
Max. Luminaires per 16A C Breaker	20

ToLEDo T8 V4 4FT 1800LM 865 25K 0029303

Max. Luminaires per 16A B Breaker	10
-----------------------------------	----

LIFETIME DATA

Lifespan L70 B50	25000
Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

PHYSICAL DATA

IP rating	IP20
Nominal Product Length (mm)	1213.6
Nominal Product Diameter (mm)	28
Weight (kg)	0.17

PACKAGING

Single packaging type	Carton
Product EAN number	5410288293035
Packaging single length / height (cm)	126.0
Packaging single width (cm)	2.8
Packaging single depth (cm)	2.8
DUN14 (outer)	15410288293032
Units per outer package	10
Packaging outer length / height (cm)	129.0
Packaging outer width (cm)	16.3
Packaging outer depth (cm)	8.5

SAFETY DATA

Optimal operating condition (°C)	-20-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

ToLEDo T8 V4 4FT 1800LM 865 25K
0029303


Energy label



18
kWh/1000h



2019/2015



18
kWh/1000h



2019/2015