



Features

- Compact and elegant design Suitable replacement for halogen, incandescent and compact fluorescent lamps Instant light at the flick of a switch Uniform light distribution Good colour rendering (CRI 80) Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas Lower maintenance costs 15,000 hours average rated life



Product Overview

Product name	ToLEDo GLS V7 1055LM 865 E27 SL
Technology	LED
Watt (Rated) (W)	9.5
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740984
Luminous flux (lm)	1055
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0
Wattage (W)	9.5
Product Voltage (V)	230
Dimmable	No

ToLEDo GLS V7 1055LM 865 E27 SL
0029591

Average life (Nominal) (h)	15000
Product EAN number	5410288295916
Warranty	3 years

Technical drawings



Data table

GENERAL DATA

Product name	ToLEDo GLS V7 1055LM 865 E27 SL
Technology	LED
Watt (Rated) (W)	9.5
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C

ToLEDo GLS V7 1055LM 865 E27 SL 0029591

Performance ambient temperature Tq (°C)	25
---	----

ETIM Class	EC001959
------------	----------

E-number FI	4740984
-------------	---------

Warranty	3 years
----------	---------

OPTICAL DATA

Luminous flux (lm)	1055
--------------------	------

Luminous flux (Rated) (lm)	1055
----------------------------	------

Colour temperature (K)	6500
------------------------	------

Light colour	Daylight
--------------	----------

CRI (Ra)	80
----------	----

Colour Variation Initial (SDCM)	6
---------------------------------	---

Photobiological Risk Group	RG0
----------------------------	-----

Lumen maintenance at end of nominal life (%)	70
--	----

ELECTRICAL DATA

Wattage (W)	9.5
-------------	-----

Equivalent watt (W)	75
---------------------	----

Product Voltage (V)	230
---------------------	-----

Control gear required	No
-----------------------	----

No. Of switching cycles before premature failures	>100000
---	---------

Transformer required	No
----------------------	----

Dimmable	No
----------	----

Inrush Current (A)	4
--------------------	---

Inrush Duration (µs)	380
----------------------	-----

Lamp Energy Label (class)	E
---------------------------	---

Nominal Frequency (Hz)	50/60Hz
------------------------	---------

Max. Luminaires per 16A C Breaker	40
-----------------------------------	----

Max. Luminaires per 16A B Breaker	20
-----------------------------------	----

LIFETIME DATA

ToLEDo GLS V7 1055LM 865 E27 SL 0029591

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

PHYSICAL DATA

Nominal Product Length (mm)	109
Nominal Product Diameter (mm)	60
Weight (kg)	0.06

PACKAGING

Single packaging type	Carton
Product EAN number	5410288295916
Packaging single length / height (cm)	11.2
Packaging single width (cm)	6.0
Packaging single depth (cm)	6.0
DUN14 (outer)	15410288295913
Units per outer package	6
Packaging outer length / height (cm)	18.8
Packaging outer width (cm)	12.7
Packaging outer depth (cm)	12.0

SAFETY DATA


Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

Energy label

**ENERG**

SYLVANIA

0029591



10
kWh/1000h




2019/2015

**ENERG**

SYLVANIA

0029591



10
kWh/1000h



2019/2015