



Features

- High performance LED PAR30 lamp with the same look and feel of traditional PAR lamps Glass construction - means no colours clashing between the lamp and fixture Reduced visible heatsink from the front Mercury-free solution Lower maintenance cost Lifetime: up to 25,000 hours High lumen efficacy Dimmable with approved dimmers* 3 year warranty Suitable for general lighting and accent lighting for hotels, restaurants, bars, lobbies, corridors and halls



Product Overview

Product name	RefLED Retro PAR30 V2 DIM 820L 840 36 SL
Technology	LED
Watt (Rated) (W)	11
Type	LED exchangeable
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4741081
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	6
Beam Angle (°)	36
Photobiological Risk Group	RG1
Wattage (W)	11
Product Voltage (V)	230

RefLED Retro PAR30 V2 DIM 820L 840 36 SL
0029199

Dimmable	Yes
Average life (Nominal) (h)	25000
Product EAN number	5410288291994
Warranty	3 years

Technical drawings



Data table

GENERAL DATA

Product name	RefLED Retro PAR30 V2 DIM 820L 840 36 SL
Technology	LED
Watt (Rated) (W)	11
Type	LED exchangeable
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Residential & Consumer, Retail
Operating temperature range (°C)	-20°C...+40°C

RefLED Retro PAR30 V2 DIM 820L 840 36 SL 0029199

Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4741081
Warranty	3 years

OPTICAL DATA

Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	6
Luminous Intensity (cd)	1900
Beam Angle (°)	36
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Wattage (W)	11
Equivalent watt (W)	95
Product Voltage (V)	230
Control gear required	No
No. Of switching cycles before premature failures	>50000
Transformer required	No
Dimmable	Yes
Inrush Current (A)	2.2
Inrush Duration (µs)	50
Lamp Energy Label (class)	F

LIFETIME DATA

Lifespan L70 B50	25000
Average life (Nominal) (h)	25000

RefLED Retro PAR30 V2 DIM 820L 840 36 SL 0029199

Average life (Rated) (h)	25000
--------------------------	-------

PHYSICAL DATA

Nominal Product Length (mm)	94
Nominal Product Diameter (mm)	95
Weight (kg)	0.234

PACKAGING

Single packaging type	Carton
Product EAN number	5410288291994
Packaging single length / height (cm)	10.3
Packaging single width (cm)	10.3
Packaging single depth (cm)	11.1
DUN14 (outer)	15410288291991
Units per outer package	6
Packaging outer length / height (cm)	33.7
Packaging outer width (cm)	24.1
Packaging outer depth (cm)	15.5

SAFETY DATA

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Dimmable with approved dimmers

Energy label



0029199



11
kWh/1000h



2019/2015



0029199



11
kWh/1000h



2019/2015