



Features

- 50,000 hours average rated lifetime Last 2.5 times longer than 54W 1149mm fluorescent tri-phosphor T5 lamp High switching cycles - 200,000X Omni-directional light distribution and wide beam angle Minimum and maximum operating temperature: -20°C to 50°C Glass construction and polycarbonate end-caps Only suitable for direct mains (AC 220-240V) operation Ideal for factories, parking lots, supermarkets, department stores, schools and offices Not suitable for operation with electronic/ECG or magnetic/CCG ballasts

Product Overview

Product name	ToLEDo Superia T5 AC V2 4FT 3900LM 840
Technology	LED
Watt (Rated) (W)	26
Lamp shape	Tube, double-ended
Type	LED exchangeable
Cap/Base	G5
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4940789
Luminous flux (lm)	3900
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Wattage (W)	26

ToLEDo Superia T5 AC V2 4FT 3900LM 840
0029257

Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	50000
IP rating	IP20
Product EAN number	5410288292571
Warranty	5 years

Technical drawings



Data table

GENERAL DATA

Product name	ToLEDo Superia T5 AC V2 4FT 3900LM 840
Technology	LED
Watt (Rated) (W)	26
Lamp shape	Tube, double-ended
Type	LED exchangeable
Cap/Base	G5
Lamp finish	Opal
Fixture rating	Open

ToLEDo Superia T5 AC V2 4FT 3900LM 840 0029257

General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
Operating temperature range (°C)	-20°C...+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4940789
Warranty	5 years

OPTICAL DATA

Luminous flux (lm)	3900
Luminous flux (Rated) (lm)	3900
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Wattage (W)	26
Product Voltage (V)	230
Lamp power factor	0.9
Control gear required	No
No. Of switching cycles before premature failures	>100000
Transformer required	No
Dimmable	No
Inrush Current (A)	18.0
Inrush Duration (µs)	6
Lamp Energy Label (class)	D

ToLEDo Superia T5 AC V2 4FT 3900LM 840 0029257

Max. Luminaires per 16A C Breaker	67
Max. Luminaires per 20A C Breaker	83
Max. Luminaires per 10A B Breaker	42
Max. Luminaires per 13A B Breaker	55
Max. Luminaires per 16A B Breaker	67

LIFETIME DATA

Lifespan L70 B50	50000
Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

PHYSICAL DATA

IP rating	IP20
Nominal Product Length (mm)	1162
Nominal Product Diameter (mm)	17
Weight (kg)	0.14

PACKAGING

Single packaging type	Carton
Product EAN number	5410288292571
Packaging single length / height (cm)	116.0
Packaging single width (cm)	2.0
Packaging single depth (cm)	2.0
DUN14 (outer)	15410288292578
Units per outer package	10
Packaging outer length / height (cm)	122.0
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	8.0

SAFETY DATA

Optimal operating condition (°C)	-20-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No




ToLEDo Superia T5 AC V2 4FT 3900LM 840
0029257

Dry applications use only	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture

Energy label

**ENERGY**
SYLVANIA
0029257




26
kWh/1000h



2019/2015

**ENERGY**
SYLVANIA
0029257



26
kWh/1000h



2019/2015