

# TOLEDO T8 V6 5FT 27W 2700LM 830 RL **0028289**





• • Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps • Omnidirectional 320° uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes • High lumen package - 2700lm • High lumen efficacy - 100 lm/W • Energy rating - A+ • Switching cycles - 200,000X • Average life 40,000 hours lifespan (L70 F50) • Wide beam angle - 220° • High power factor - 0.90 • Suitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots and maintenance free applications • Suitable for operation with electromagnetic gears and direct mains operation (220-240V) • 3-Year warranty.



Product name	TOLEDO T8 V6 5FT 27W 2700LM 830 RL
110000	
Technology	LED
Watt (Rated) (W)	27
Cap/Base	G13
General application	Hospitality, Logistics & Industry, Residential &
	Consumer
ETIM Class	EC001959
E-number FI	4940744
Luminous flux (lm)	2700
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Wattage (W)	27
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	40000
Product EAN number	5410288282893



## TOLEDO T8 V6 5FT 27W 2700LM 830 RL

### 0028289

Warranty 3 years

### Data table

### **GENERAL DATA**

Product name	TOLEDO T8 V6 5FT 27W 2700LM 830 RL
Technology	LED
Watt (Rated) (W)	27
Cap/Base	G13
General application	Hospitality, Logistics & Industry, Residential &
	Consumer
ETIM Class	EC001959
E-number FI	4940744
Warranty	3 years

### **OPTICAL DATA**

Luminous flux (lm)	2700
Luminous flux (Rated) (Im)	2700
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

### **ELECTRICAL DATA**

Wattage (W)	27
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max)	0.5
(s)	
Product Voltage (V)	230
Lamp power factor	0.9
Control gear required	No
No. Of switching cycles before	>200000
premature failures	



# TOLEDO T8 V6 5FT 27W 2700LM 830 RL

### 0028289

Dimmable	No
----------	----

### LIFETIME DATA

Average life (Nominal) (h)	40000
Average life (Rated) (h)	40000

#### PHYSICAL DATA

### **PACKAGING**

Single packaging type	Carton
Product EAN number	5410288282893
Packaging single length / height (cm)	155.2
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (outer)	15410288282890
Units per outer package	10
Packaging outer length / height (cm)	159.7
Packaging outer width (cm)	22.6
Packaging outer depth (cm)	11.7

### **SAFETY DATA**

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture