

Features

- Integrated LED highbay; Black aluminium housing; 19500Lm; 120 W; 163 Lm/W; 6500K; Drive current: 470mA; CRI 80; 85° beam angle; 0-10V dimmable; IP65; IK08; Lifespan L80:B50 90,000 hrs; (D x H) 298 x 168 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.


Product Overview

Product name	Granit IP65 0-10V 19500lm 865 WB
Technology	LED
General application	Logistics & Industry
ETIM Class	EC001716
E-number FI	4357103
Fixture luminous flux (lm)	19500
Luminaire efficacy (lm/W)	163
Colour temperature (K)	6500
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	85
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	120
Electrical protection	Class I
Dimmable	Yes
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL9017
IP rating	IP65

Granit IP65 0-10V 19500lm 865 WB
0039737

IK rating	IK08
Product EAN number	5410288397375
Warranty	5 years
Dimming method	0-10V

Photometry



Data table

GENERAL DATA

Product name	Granit IP65 0-10V 19500lm 865 WB
Technology	LED
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
ETIM Class	EC001716
E-number FI	4357103
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	19500
Luminaire efficacy (lm/W)	163
Colour temperature (K)	6500

Granit IP65 0-10V 19500lm 865 WB 0039737

Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	85
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	120
Mains voltage (V)	220-240V
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear required	No
No. Of switching cycles before premature failures	>100000
Dimmable	Yes
Dimming method	0-10V
Drive current (mA)	470
Inrush Current (A)	80
Inrush Duration (µs)	300
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. Luminaires per 10A C Breaker	5
Max. Luminaires per 13A C Breaker	6
Max. Luminaires per 16A C Breaker	9
Max. Luminaires per 20A C Breaker	11
Max. Luminaires per 10A B Breaker	3
Max. Luminaires per 13A B Breaker	7
Max. Luminaires per 16A B Breaker	5

Granit IP65 0-10V 19500lm 865 WB 0039737

Max. Luminaires per 20A B Breaker	6
Mains surge immunity (differential mode -> L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	6

LIFETIME DATA

Lifespan L80 B50	90000
Lifespan L80 B20	82000
Lifespan L90 B50	44000

PHYSICAL DATA

Housing colour	RAL9017
IP rating	IP65
IK rating	IK08
Nominal Product Height (mm)	168
Nominal Product Diameter (mm)	298
Weight (kg)	2.243

PACKAGING

Single packaging type	Carton
Product EAN number	5410288397375
Packaging single length / height (cm)	32.5
Packaging single width (cm)	32.5
Packaging single depth (cm)	14.5
DUN14 (outer)	05410288397375
Units per outer package	1
Packaging outer length / height (cm)	32.5
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	14.5

SAFETY DATA

Optimal operating condition (°C)	-30-50
----------------------------------	--------



Granit IP65 0-10V 19500lm 865 WB
0039737

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No