


Start Flood Flat IP65 1000LM 840 Black
0050106



Features

- The streamlined, durable, lightweight die-cast aluminium body makes Start Flood Flat a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black (RAL9017) housing, white reflector, 1000 lm, 9 W, 111 lm/W, 4000K, non dimmable, CRI>80, IP65, IK06, Class I, lifespan L70:B50: 90000 hrs, 100 x 105 x 23 mm (L x W x H). Weight: 0.32kg.


Product Overview

Product name	Start Flood Flat IP65 1000LM 840 Black
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Wall surface mounted, Ceiling surface mounting
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4579527
Fixture luminous flux (lm)	1000
Luminaire efficacy (lm/W)	111
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	110
Photobiological Risk Group	RG1
Total power consumption (W)	9
Electrical protection	Class I

Start Flood Flat IP65 1000LM 840 Black
0050106


Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Low (6% - 20%)
Housing colour	Black
IP rating	IP65
IK rating	IK06
Product EAN number	5410288501062
Warranty	3 years
Dimming method	N/A

Photometry



Start Flood Flat IP65 1000LM 840 Black 0050106

Technical drawings



Data table

GENERAL DATA

Product name	Start Flood Flat IP65 1000LM 840 Black
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Wall surface mounted, Ceiling surface mounting
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC001744
E-number FI	4579527
Warranty	3 years

OPTICAL DATA

Fixture luminous flux (lm)	1000
Luminaire efficacy (lm/W)	111
Colour temperature (K)	4000
Light colour	Neutral White

Start Flood Flat IP65 1000LM 840 Black 0050106

CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	110
Distribution type	Symmetric
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	9
Mains voltage (V)	220-240V
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	20
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	19
Inrush Current (A)	18
Inrush Duration (μ s)	125
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. Luminaires per 10A C Breaker	17
Max. Luminaires per 13A C Breaker	22
Max. Luminaires per 16A C Breaker	28
Max. Luminaires per 20A C Breaker	34
Max. Luminaires per 10A B Breaker	10
Max. Luminaires per 13A B Breaker	13
Max. Luminaires per 16A B Breaker	17
Max. Luminaires per 20A B Breaker	21

LIFETIME DATA

Start Flood Flat IP65 1000LM 840 Black 0050106

Lifespan L70 B50	90000
Lifespan L80 B50	85000
Lifespan L80 B20	54000

PHYSICAL DATA

Housing colour	Black
IP rating	IP65
IK rating	IK06
Diffuser finish	Transparent
Diffuser material	Safety tempered glass
Reflector finish	White
Nominal Product Length (mm)	100
Nominal Product Width (mm)	105
Nominal Product Height (mm)	23
Weight (kg)	0.32

PACKAGING

Single packaging type	Carton
Product EAN number	5410288501062
Packaging single length / height (cm)	13.0
Packaging single width (cm)	5.5
Packaging single depth (cm)	15.5
DUN14 (outer)	15410288501069
Units per outer package	6
Packaging outer length / height (cm)	36.0
Packaging outer width (cm)	14.5
Packaging outer depth (cm)	17.5

SAFETY DATA

Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No

SYLVANIA

Start Flood Flat IP65 1000LM 840 Black
0050106

Light your world