

START WATERPROOF 1200 HOUSING 1X
0047922



Features


• • Luminaire, polycarbonate housing • Single version, 1200mm • Protection type IP65 • Luminous flux and light colour vary depending on LED tubes used • To be used with T8 LED tubes • Easy to install with stainless steel fixing brackets included for ceiling mounting • Ideal for any industrial facilities, garages, car parks, workshops.

Product Overview

Product name	START WATERPROOF 1200 HOUSING 1X
Technology	LED
Cap/Base	G13
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Fixture rating	Enclosed
Light source included	Fixture without Lightsource
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4309056
LOR (%)	75
Electrical protection	Class I
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288479224
Warranty	3 years

START WATERPROOF 1200 HOUSING 1X 0047922

Technical drawings



Data table

GENERAL DATA

Product name	START WATERPROOF 1200 HOUSING 1X
Technology	LED
Cap/Base	G13
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4309056
Warranty	3 years

OPTICAL DATA

LOR (%)	75
---------	----

ELECTRICAL DATA

Light source included	Fixture without Lightsource
Electrical protection	Class I
Control gear required	No
Glow Wire Test (°C)	650

START WATERPROOF 1200 HOUSING 1X 0047922

PHYSICAL DATA

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1260
Nominal Product Width (mm)	69
Nominal Product Height (mm)	78
Weight (kg)	0.81

PACKAGING

Single packaging type	Carton
Product EAN number	5410288479224
Packaging single length / height (cm)	128.0
Packaging single width (cm)	6.9
Packaging single depth (cm)	5.2
DUN14 (outer)	15410288479221
Units per outer package	1
Packaging outer length / height (cm)	128.0
Packaging outer width (cm)	6.9
Packaging outer depth (cm)	5.2

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No