

START Waterproof Tubular 1200 IP66 3900lm 830 PC
0047157



Features

- START Waterproof Tubular is an aesthetically attractive integrated LED fixture. Easy to install with 304 stainless steel fixing brackets for ceiling mounting. Polycarbonate housing; 3000K; 35W; 3900lm; 111lm/W and lumen maintenance L70:B50 of 68,000 hours lifetime. IP66; IK10; Class I; 1190mm x 62mm. Can be suspended with additional accessory (SKU 0046035).


Product Overview

Product name	START Waterproof Tubular 1200 IP66 3900lm 830 PC
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate, Polyester
General application	Logistics & Industry
ETIM Class	EC000109
E-number FI	4357128
Fixture luminous flux (lm)	3900
Luminaire efficacy (lm/W)	111
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Beam Angle (°)	120
Photobiological Risk Group	RG1
Total power consumption (W)	35
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Housing colour	White
IP rating	IP66
IK rating	IK10
Product EAN number	5410288471570


**START Waterproof Tubular 1200 IP66 3900lm 830 PC
0047157**

Warranty	5 years
Dimming method	N/A

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	START Waterproof Tubular 1200 IP66 3900lm 830 PC
Technology	LED
Cap/Base	N/A

START Waterproof Tubular 1200 IP66 3900lm 830 PC 0047157

Housing	PC Polycarbonate, Polyester
General application	Logistics & Industry
Operating temperature range (°C)	-25°C...+50°C
ETIM Class	EC000109
E-number FI	4357128
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	3900
Luminaire efficacy (lm/W)	111
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Beam Angle (°)	120
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	35
Mains voltage (V)	220-240V
Lamp power factor	0.9
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	350
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	19
Max. Luminaires per 13A C Breaker	26
Max. Luminaires per 16A C Breaker	31
Max. Luminaires per 20A C Breaker	39

START Waterproof Tubular 1200 IP66 3900lm 830 PC 0047157

Max. Luminaires per 10A B Breaker	11
Max. Luminaires per 13A B Breaker	15
Max. Luminaires per 16A B Breaker	19
Max. Luminaires per 20A B Breaker	23

LIFETIME DATA

Lifespan L70 B50	68000
Lifespan L80 B50	50000
Lifespan L80 B20	42800

PHYSICAL DATA

Housing colour	White
IP rating	IP66
IK rating	IK10
Nominal Product Length (mm)	1190
Nominal Product Diameter (mm)	62
Weight (kg)	1.24

PACKAGING

Single packaging type	Carton
Product EAN number	5410288471570
Packaging single length / height (cm)	127.0
Packaging single width (cm)	7.4
Packaging single depth (cm)	7.4
DUN14 (outer)	15410288471577
Units per outer package	6
Packaging outer length / height (cm)	128.5
Packaging outer width (cm)	24.2
Packaging outer depth (cm)	17.0

SAFETY DATA

Optimal operating condition (°C)	-25-50
Special purpose lamp	No



START Waterproof Tubular 1200 IP66 3900lm 830 PC
0047157

Dry applications use only	No
Suitable for household illumination	No