


OptiClip 1200 4000K C9 WH CC WHITE
0044020



Features

• OPTICLIP 1200 4000K C9 WH CC WHITE is a high efficacy low glare luminaire with replaceable light engines for office and education applications. Ceiling recessed LED luminaire with white colour plastic optic, direct light distribution, luminaire dimensions: 1195x295x20mm, Sylvania White body colour (RAL9016), IP40 (from the front), IK07, Constant Current driver, low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 3250lm luminous flux, 29W power consumption, 112lm/W system efficacy, CRI>90, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<20, Luminance at 65° < 2000 cd/m2, lifespan: 62,000 hours L80B20, photobiological safety risk group 1. Electrical protection Class II. Glow wire test 850°C.


Product Overview

Product name	OptiClip 1200 4000K C9 WH CC WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Education, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	3250
Luminaire efficacy (lm/W)	112
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Beam Angle (°)	80
Glare control	< 20

OptiClip 1200 4000K C9 WH CC WHITE
0044020


Photobiological Risk Group	RG1
Total power consumption (W)	29
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK07
Product EAN number	5410288440200
Warranty	5 years
Dimming method	N/A

Photometry



OptiClip 1200 4000K C9 WH CC WHITE
0044020

Technical drawings



Data table

GENERAL DATA

Product name	OptiClip 1200 4000K C9 WH CC WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Education, Office
Operating temperature range (°C)	-20°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	3250
Luminaire efficacy (lm/W)	112
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Luminous Intensity (cd)	1900

OptiClip 1200 4000K C9 WH CC WHITE 0044020

Beam Angle (°)	80
Distribution type	Symmetric
Glare control	< 20
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	29
Mains voltage (V)	220-240V
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	10
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Transformer required	No
Dimmable	No
Dimming method	N/A
Drive current (mA)	800
Inrush Current (A)	35
Inrush Duration (μ s)	200
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	E, E(more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	19
Max. Luminaires per 13A C Breaker	24
Max. Luminaires per 16A C Breaker	31
Max. Luminaires per 20A C Breaker	39
Max. Luminaires per 10A B Breaker	11
Max. Luminaires per 16A B Breaker	19
Max. Luminaires per 20A B Breaker	23

LIFETIME DATA

OptiClip 1200 4000K C9 WH CC WHITE 0044020

Lifespan L70 B50	100000
Lifespan L80 B20	62500

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1195
Nominal Product Width (mm)	295
Nominal Product Height (mm)	20
Weight (kg)	2.8

PACKAGING

Single packaging type	Carton
Product EAN number	5410288440200
Packaging single length / height (cm)	120.0
Packaging single width (cm)	4.0
Packaging single depth (cm)	30.0
DUN14 (outer)	05410288440200
Units per outer package	1
Packaging outer length / height (cm)	120.0
Packaging outer width (cm)	4.0
Packaging outer depth (cm)	30.0

SAFETY DATA

Optimal operating condition (°C)	-20-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No