

RANA LINEAR R 32 4K MPO SSC01 W
0052477



Features

- Ceiling recessed LED Linear luminaire with MicroPrismatic Optic, Dimensions: 1154mm x 90mm x 91mm, Direct, White Body, SylSmart Standalone capable, Electric Class 1, Neutral White LED (4000K), 3100lm, 32W, 97lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse), Low LED Flicker (+/-5%), UGR<21, L90B10 at 50,000 hours, Glow Wire Test 850°C, Can be covered with building insulation of Glass Wool type.

Product Overview

Product name	RANA LINEAR R 32 4K MPO SSC01 W
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Environment	Internal
General application	Education, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	3100
Luminous flux (lm)	3100
Luminaire efficacy (lm/W)	97
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 21
Photobiological Risk Group	RG0
Total power consumption (W)	32
Electrical protection	Class I

RANA LINEAR R 32 4K MPO SSC01 W 0052477

Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288524771
Warranty	5 years
Dimming method	SylSmart SSC

Data table

GENERAL DATA

Product name	RANA LINEAR R 32 4K MPO SSC01 W
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Environment	Internal
General application	Education, Office
Operating temperature range (°C)	-25°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	3100
Luminous flux (lm)	3100
Luminaire efficacy (lm/W)	97
LOR (%)	100
Colour temperature (K)	4000

RANA LINEAR R 32 4K MPO SSC01 W 0052477

Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Adjustable chromaticity	N
Distribution type	Symmetric
Glare control	< 21
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	32
Mains voltage (V)	220-240V
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	10
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic ballast
Transformer required	Yes
Dimmable	Yes
Dimming method	SylSmart SSC
Minimum dimming level (%)	1
Drive current (mA)	600
Inrush Current (A)	20
Inrush Duration (μ s)	25
Glow Wire Test ($^{\circ}$ C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	57
Max. Luminaires per 13A C Breaker	71
Max. Luminaires per 16A C Breaker	93
Max. Luminaires per 20A C Breaker	114
Max. Luminaires per 10A B Breaker	35

RANA LINEAR R 32 4K MPO SSC01 W 0052477

Max. Luminaires per 13A B Breaker	45
Max. Luminaires per 16A B Breaker	55
Max. Luminaires per 20A B Breaker	68

LIFETIME DATA

Lifespan L70 B50	72000
Lifespan L70 B20	60000
Lifespan L70 B10	72000
Lifespan L80 B50	72000
Lifespan L80 B20	60000
Lifespan L80 B10	72000
Lifespan L90 B50	72000
Lifespan L90 B20	50000
Lifespan L90 B10	46000

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Prismatic
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1150
Nominal Product Width (mm)	90
Nominal Product Height (mm)	91
Cutout Dimensions (W x L in mm or Diameter in mm)	72
Weight (kg)	3.15
Recessed Depth (mm)	90

PACKAGING

Single packaging type	Carton
Product EAN number	5410288524771
Packaging single length / height (cm)	117.0
Packaging single width (cm)	10.5



RANA LINEAR R 32 4K MPO SSC01 W
0052477

Packaging single depth (cm)	11.5
DUN14 (outer)	05410288524771
Units per outer package	1
Packaging outer length / height (cm)	117.0
Packaging outer width (cm)	10.5
Packaging outer depth (cm)	11.5

SAFETY DATA

Optimal operating condition (°C)	-25-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No