

SYLFIRE LED TILTABLE 830 DIM WHITE DC
0059827



Features

- IP20 LED downlight, fire rated for 30, 60 and 90 minutes. 8W up to 620 lumen output.

Product Overview

Product name	SYLFIRE LED TILTABLE 830 DIM WHITE DC
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Residential & Consumer
ETIM Class	EC001744
Fixture luminous flux (lm)	730
Luminaire efficacy (lm/W)	91
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	40
Photobiological Risk Group	RG1
Total power consumption (W)	8
Product Voltage (V)	42
Electrical protection	Class II
Dimmable	Yes
Minimum dimming level (%)	10
Housing colour	White
IP rating	IP20

SYLFIRE LED TILTABLE 830 DIM WHITE DC 0059827

IK rating	IK06
Product EAN number	5410288598277
Warranty	5 years
Colour Code	830
Dimming method	Mains: leading / trailing edge

Data table

GENERAL DATA

Product name	SYLFIRE LED TILTABLE 830 DIM WHITE DC
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Residential & Consumer
Operating temperature range (°C)	-10°C...+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	730
Luminaire efficacy (lm/W)	91
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	40
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

SYLFIRE LED TILTABLE 830 DIM WHITE DC 0059827

ELECTRICAL DATA

Total power consumption (W)	8
Mains voltage (V)	220-240V
Product Voltage (V)	42
Lamp power factor	0.85
Electrical protection	Class II
Control gear required	No
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Minimum dimming level (%)	10
Drive current (mA)	150
Inrush Current (A)	10
Inrush Duration (µs)	150
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	60
Max. Luminaires per 13A C Breaker	80
Max. Luminaires per 16A C Breaker	100
Max. Luminaires per 20A C Breaker	120

LIFETIME DATA

Lifespan L70 B50	50000
------------------	-------

PHYSICAL DATA

Housing colour	White
IP rating	IP20
IK rating	IK06
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Height (mm)	117
Nominal Product Diameter (mm)	92
Cutout Dimensions (W x L in mm or Diameter in mm)	86



SYLFIRE LED TILTABLE 830 DIM WHITE DC
0059827

Weight (kg)	0.479
-------------	-------

PACKAGING

Single packaging type	Carton
Product EAN number	5410288598277
Packaging single length / height (cm)	13.5
Packaging single width (cm)	13.0
Packaging single depth (cm)	13.03
DUN14 (outer)	05410288598277
Units per outer package	20
Packaging outer length / height (cm)	68.2
Packaging outer width (cm)	29.7
Packaging outer depth (cm)	29.9

SAFETY DATA

Optimal operating condition (°C)	-10-45
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No