

OPTIX LINEAR SURFACE 1200 LUMI 4K ALU SSC 2023854



Features

- OPTIX LINEAR SURFACE 1200 LUMI 4000K ALU SSC is a surface mounted linear luminaire for office and education applications with Aluminised plastic extra low glare optics and RAL9016 colour fixture body. SylSmart Standalone enabled. 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. For 4000K - Colour rendering index Ra >98; Melanopic Ratio MEER: 0.778; Fidelity Index R#: 94; Gamut Index R#: 98. For 4000K luminous flux: 2850lm. Power consumption: 31W. Luminaire efficacy: 92lm/W. UGR<19 Luminance at 65°<200 Cd/m2, IK07, IP20. Photobiological safety risk group 0. Electrical protection Class I. Glow wire test 850°C. 60,000hrs L80B20 lifespan.

Product Overview

Product name	OPTIX LINEAR SURFACE 1200 LUMI 4K ALU SSC
Technology	LED LumiNature
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Education, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	2870
Luminaire efficacy (lm/W)	93
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	98
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	31
Electrical protection	Class I

OPTIX LINEAR SURFACE 1200 LUMI 4K ALU SSC 2023854

Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238545
Warranty	5 years
Dimming method	SylSmart SSC

Data table

GENERAL DATA

Product name	OPTIX LINEAR SURFACE 1200 LUMI 4K ALU SSC
Technology	LED LumiNature
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Education, Office
Operating temperature range (°C)	10°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	2870
Luminaire efficacy (lm/W)	93
Colour temperature (K)	4000
Correlated colour temperature range (K)	2800 - 6200
Light colour	Neutral White
CRI (Ra)	98
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3

OPTIX LINEAR SURFACE 1200 LUMI 4K ALU SSC 2023854

Glare control	< 19
---------------	------

Photobiological Risk Group	RG1
----------------------------	-----

ELECTRICAL DATA

Total power consumption (W)	31
-----------------------------	----

Mains voltage (V)	220-240V
-------------------	----------

Lamp power factor	0.98
-------------------	------

Electrical protection	Class I
-----------------------	---------

Control gear required	No
-----------------------	----

Control gear type	LED driver constant current
-------------------	-----------------------------

Transformer required	No
----------------------	----

Dimmable	Yes
----------	-----

Dimming method	SylSmart SSC
----------------	--------------

Drive current (mA)	200
--------------------	-----

Inrush Current (A)	29
--------------------	----

Inrush Duration (µs)	180
----------------------	-----

Glow Wire Test (°C)	850
---------------------	-----

Energy Efficiency Class (A->G) of contained light source	F
--	---

Nominal Frequency (Hz)	50/60Hz
------------------------	---------

Max. Luminaires per 10A C Breaker	21
-----------------------------------	----

Max. Luminaires per 13A C Breaker	28
-----------------------------------	----

Max. Luminaires per 16A C Breaker	36
-----------------------------------	----

Max. Luminaires per 20A C Breaker	45
-----------------------------------	----

Max. Luminaires per 10A B Breaker	13
-----------------------------------	----

Max. Luminaires per 13A B Breaker	17
-----------------------------------	----

Max. Luminaires per 16A B Breaker	22
-----------------------------------	----

Max. Luminaires per 20A B Breaker	27
-----------------------------------	----

LIFETIME DATA

Lifespan L70 B50	100000
------------------	--------

Lifespan L80 B20	60000
------------------	-------

PHYSICAL DATA

OPTIX LINEAR SURFACE 1200 LUMI 4K ALU SSC 2023854

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1129
Nominal Product Width (mm)	90
Nominal Product Height (mm)	80
Weight (kg)	3.25

PACKAGING

Single packaging type	Carton
Product EAN number	5025768238545
Packaging single length / height (cm)	119.0
Packaging single width (cm)	10.0
Packaging single depth (cm)	11.0
DUN14 (outer)	05025768238545
Units per outer package	1
Packaging outer length / height (cm)	119.0
Packaging outer width (cm)	10.0
Packaging outer depth (cm)	11.0

SAFETY DATA

Optimal operating condition (°C)	10-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No