



Features

- MYRIAD IP65 3000K PHASE DIM WHITE

Product Overview

Product name	MYRIAD IP65 3000K PHASE DIM WHITE
Technology	LED
Mount	Ceiling recessed mounting
Environment	Interior
General application	Hospitality, Office, Retail
ETIM Class	EC001744
E-number SE	7462013
E-number Norway	3290231
Fixture luminous flux (lm)	1069
Luminaire efficacy (lm/W)	107
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Beam Angle (°)	30
Photobiological Risk Group	RG1
Total power consumption (W)	10
Electrical protection	Class II
Control gear type	Other
Control gear mounting	Integral
IP rating	IP65/20

MYRIAD IP65 3000K PHASE DIM WHITE 2049525

IK rating	IK02
Product EAN number	5025768495252
Warranty	5 years
Dimming method	Mains: leading / trailing edge

Data table

GENERAL DATA

Product name	MYRIAD IP65 3000K PHASE DIM WHITE
Technology	LED
Mount	Ceiling recessed mounting
Environment	Interior
General application	Hospitality, Office, Retail
ETIM Class	EC001744
E-number SE	7462013
E-number Norway	3290231
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	1069
Luminaire efficacy (lm/W)	107
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	30
Distribution type	Symmetric
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	10
Mains voltage (V)	220-240V

MYRIAD IP65 3000K PHASE DIM WHITE 2049525

Electrical protection	Class II
Control gear required	No
Control gear type	Other
Control gear mounting	Integral
Transformer required	Yes
Dimming method	Mains: leading / trailing edge
Drive current (mA)	250
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B10	68500

PHYSICAL DATA

IP rating	IP65/20
IK rating	IK02
Diffuser material	Glass
Nominal Product Height (mm)	72
Nominal Product Diameter (mm)	76
Cutout Dimensions (W x L in mm or Diameter in mm)	75
Weight (kg)	0.39
Recessed Depth (mm)	72

PACKAGING

Single packaging type	Carton
Product EAN number	5025768495252
Packaging single length / height (cm)	17.5
Packaging single width (cm)	15.0
Packaging single depth (cm)	17.5
Units per outer package	1

Concord

MYRIAD IP65 3000K PHASE DIM WHITE 2049525

Packaging outer length / height (cm)	17.5
Packaging outer width (cm)	15.0
Packaging outer depth (cm)	17.5

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No