

MYRIAD DECO HOUSING FLOOD 3000K PHDM WHITE REF 2057997



Features

- The Myriad Housing 3000K Flood accent downlight is a high efficient 10W recessed spotlight, luminous flux: 1037lm, luminaire efficacy 104lm/W. Colour rendering index Ra>80, Colour temperature 3000K, Beam angle 46°, Protection rating IP20, Cut out dimensions: 76mm.

Product Overview

Product name	MYRIAD DECO HOUSING FLOOD 3000K PHDM WHITE REF
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Interior
General application	Hospitality, Office, Residential & Consumer, Retail
ETIM Class	EC001744
Fixture luminous flux (lm)	1037
Luminaire efficacy (lm/W)	104
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Beam Angle (°)	46
Photobiological Risk Group	RG1
Total power consumption (W)	10
Electrical protection	Class II
Control gear type	Electronic ballast
Minimum dimming level (%)	10
Housing colour	White

MYRIAD DECO HOUSING FLOOD 3000K PHDM WHITE REF 2057997

IP rating	IP20
IK rating	IK02
Product EAN number	5025768579976
Warranty	5 years
Dimming method	Other

Data table

GENERAL DATA

Product name	MYRIAD DECO HOUSING FLOOD 3000K PHDM WHITE REF
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Interior
General application	Hospitality, Office, Residential & Consumer, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	1037
Luminaire efficacy (lm/W)	104
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	46
Photobiological Risk Group	RG1

ELECTRICAL DATA

MYRIAD DECO HOUSING FLOOD 3000K PHDM WHITE REF 2057997

Total power consumption (W)	10
Mains voltage (V)	230-240V
Electrical protection	Class II
Control gear required	No
Control gear type	Electronic ballast
Transformer required	Yes
Dimming method	Other
Minimum dimming level (%)	10
Drive current (mA)	250
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B10	68500

PHYSICAL DATA

Housing colour	White
IP rating	IP20
IK rating	IK02
Nominal Product Height (mm)	72
Cutout Dimensions (W x L in mm or Diameter in mm)	76
Weight (kg)	0.39
Recessed Depth (mm)	72

PACKAGING

Single packaging type	Carton
Product EAN number	5025768579976
Packaging single length / height (cm)	17.5
Packaging single width (cm)	15.0
Packaging single depth (cm)	17.5

MYRIAD DECO HOUSING FLOOD 3000K PHDM WHITE REF 2057997

DUN14 (outer)	05025768579976
Units per outer package	1
Packaging outer length / height (cm)	17.5
Packaging outer width (cm)	15.0
Packaging outer depth (cm)	17.5

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No