

## COLOSSAL 400mm 830 PRISM DIR+HAL WHITE 2071136



### Features

- 400mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with PMMA prismatic diffuser. Direct/indirect (halo) light distribution, 1920lm luminuous flux, 16W system power, 120lm/W luminaire efficacy. Constant current driver. Colour rendering index Ra >80, 3000K Warm White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40, IK03. 350mA drive current. UGR≤19. Electrical protection Class1, 220-240V. Reported lifetime 66k hours L90B10.

### Product Overview

|                                 |                                        |
|---------------------------------|----------------------------------------|
| Product name                    | COLOSSAL 400mm 830 PRISM DIR+HAL WHITE |
| Technology                      | LED (3 SDCM)                           |
| Cap/Base                        | N/A                                    |
| Housing                         | Aluminium                              |
| Mount                           | Suspended                              |
| General application             | Hospitality, Office                    |
| ETIM Class                      | EC002892                               |
| Fixture luminous flux (lm)      | 1920                                   |
| Luminaire efficacy (lm/W)       | 120                                    |
| Colour temperature (K)          | 3000                                   |
| Light colour                    | Warm White                             |
| CRI (Ra)                        | 80                                     |
| Colour Variation Initial (SDCM) | 3                                      |
| Glare control                   | < 19                                   |
| Photobiological Risk Group      | RG0                                    |
| Total power consumption (W)     | 16                                     |
| Electrical protection           | Class I                                |
| Control gear type               | LED driver constant current            |
| Dimmable                        | No                                     |
| LED Flickering Rate             | Medium (21% - 40%)                     |
| Housing colour                  | RAL 9016 - Traffic white / Bezel       |

# Concord

## COLOSSAL 400mm 830 PRISM DIR+HAL WHITE 2071136

|                    |               |
|--------------------|---------------|
| IP rating          | IP40/20       |
| IK rating          | IK07          |
| Product EAN number | 5025768711369 |
| Warranty           | 5 years       |
| Colour Code        | 830           |
| Dimming method     | N/A           |

### Data table

#### GENERAL DATA

|                                  |                                        |
|----------------------------------|----------------------------------------|
| Product name                     | COLOSSAL 400mm 830 PRISM DIR+HAL WHITE |
| Technology                       | LED (3 SDCM)                           |
| Cap/Base                         | N/A                                    |
| Housing                          | Aluminium                              |
| Mount                            | Suspended                              |
| General application              | Hospitality, Office                    |
| Operating temperature range (°C) | 10°C...+25°C                           |
| ETIM Class                       | EC002892                               |
| Warranty                         | 5 years                                |

#### OPTICAL DATA

|                                 |            |
|---------------------------------|------------|
| Fixture luminous flux (lm)      | 1920       |
| Luminaire efficacy (lm/W)       | 120        |
| Colour temperature (K)          | 3000       |
| Colour Code                     | 830        |
| Light colour                    | Warm White |
| CRI (Ra)                        | 80         |
| Colour Variation Initial (SDCM) | 3          |
| Distribution type               | Symmetric  |
| Glare control                   | < 19       |
| Photobiological Risk Group      | RG0        |

#### ELECTRICAL DATA

|                             |    |
|-----------------------------|----|
| Total power consumption (W) | 16 |
|-----------------------------|----|

# Concord

## COLOSSAL 400mm 830 PRISM DIR+HAL WHITE 2071136

|                                                                       |                             |
|-----------------------------------------------------------------------|-----------------------------|
| Mains voltage (V)                                                     | 220-240V                    |
| Lamp power factor                                                     | 0.93                        |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x % | 20                          |
| Electrical protection                                                 | Class I                     |
| Control gear required                                                 | No                          |
| Control gear type                                                     | LED driver constant current |
| Transformer required                                                  | No                          |
| Dimmable                                                              | No                          |
| Dimming method                                                        | N/A                         |
| Drive current (mA)                                                    | 350                         |
| Inrush Current (A)                                                    | 8                           |
| Inrush Duration ( $\mu$ s)                                            | 80                          |
| Glow Wire Test ( $^{\circ}$ C)                                        | 650                         |
| Energy Efficiency Class (A->G) of contained light source              | B                           |
| Nominal Frequency (Hz)                                                | 50/60Hz                     |
| LED Flickering Rate                                                   | Medium (21% - 40%)          |
| Max. Luminaires per 10A C Breaker                                     | 65                          |
| Max. Luminaires per 13A C Breaker                                     | 80                          |
| Max. Luminaires per 16A C Breaker                                     | 100                         |
| Max. Luminaires per 20A C Breaker                                     | 125                         |
| Max. Luminaires per 10A B Breaker                                     | 65                          |
| Max. Luminaires per 13A B Breaker                                     | 80                          |
| Max. Luminaires per 16A B Breaker                                     | 100                         |
| Max. Luminaires per 20A B Breaker                                     | 125                         |

### LIFETIME DATA

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 170000 |
| Lifespan L80 B20 | 145000 |
| Lifespan L90 B10 | 66000  |

### PHYSICAL DATA

|                |                                  |
|----------------|----------------------------------|
| Housing colour | RAL 9016 - Traffic white / Bezel |
|----------------|----------------------------------|

# Concord

## COLOSSAL 400mm 830 PRISM DIR+HAL WHITE 2071136

|                               |              |
|-------------------------------|--------------|
| IP rating                     | IP40/20      |
| IK rating                     | IK07         |
| Diffuser finish               | Prismatic    |
| Diffuser material             | PMMA Acrylic |
| Nominal Product Height (mm)   | 93           |
| Nominal Product Diameter (mm) | 400          |
| Weight (kg)                   | 6.5          |

### PACKAGING

|                                       |                |
|---------------------------------------|----------------|
| Single packaging type                 | Carton         |
| Product EAN number                    | 5025768711369  |
| Packaging single length / height (cm) | 14.0           |
| Packaging single width (cm)           | 47.0           |
| Packaging single depth (cm)           | 47.0           |
| DUN14 (outer)                         | 05025768711369 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 14.0           |
| Packaging outer width (cm)            | 47.0           |
| Packaging outer depth (cm)            | 47.0           |

### SAFETY DATA

|                                     |       |
|-------------------------------------|-------|
| Optimal operating condition (°C)    | 10-25 |
| Special purpose lamp                | No    |
| Dry applications use only           | No    |
| Suitable for household illumination | No    |