

## COLOSSAL 1200mm 940 OPAL DIR WHITE DALI 2071297



### Features

- 1200mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with polycarbonate opal diffuser. Direct light distribution, 18745lm luminous flux, 153.6W system power, 122lm/W luminaire efficacy. DALI dimmable. Colour rendering index Ra >90, 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40/IP20, IK03. 450mA drive current. Electrical protection Class1, 220-240V. Reported lifetime 66k hours L90B10.

### Product Overview

|                                 |                                         |
|---------------------------------|-----------------------------------------|
| Product name                    | COLOSSAL 1200mm 940 OPAL DIR WHITE DALI |
| Technology                      | LED (3 SDCM)                            |
| Cap/Base                        | N/A                                     |
| Housing                         | Aluminium                               |
| Mount                           | Ceiling surface mounting                |
| General application             | Hospitality, Office                     |
| ETIM Class                      | EC002892                                |
| Fixture luminous flux (lm)      | 18745                                   |
| Luminaire efficacy (lm/W)       | 122                                     |
| Colour temperature (K)          | 4000                                    |
| Light colour                    | Neutral White                           |
| CRI (Ra)                        | 90                                      |
| Colour Variation Initial (SDCM) | 3                                       |
| Glare control                   | < 22                                    |
| Photobiological Risk Group      | RG0                                     |
| Total power consumption (W)     | 153.6                                   |
| Electrical protection           | Class I                                 |
| Control gear type               | LED driver constant current             |
| Dimmable                        | Yes                                     |
| LED Flickering Rate             | Ultra low (5% or less)                  |
| Housing colour                  | RAL 9016 - Traffic white / Bezel        |
| IP rating                       | IP40/20                                 |

## COLOSSAL 1200mm 940 OPAL DIR WHITE DALI 2071297

|                    |               |
|--------------------|---------------|
| IK rating          | IK07          |
| Product EAN number | 5025768712977 |
| Warranty           | 5 years       |
| Colour Code        | 940           |
| Dimming method     | DALI          |

### Data table

#### GENERAL DATA

|                                  |                                         |
|----------------------------------|-----------------------------------------|
| Product name                     | COLOSSAL 1200mm 940 OPAL DIR WHITE DALI |
| Technology                       | LED (3 SDCM)                            |
| Cap/Base                         | N/A                                     |
| Housing                          | Aluminium                               |
| Mount                            | Ceiling surface mounting                |
| General application              | Hospitality, Office                     |
| Operating temperature range (°C) | 5°C...+25°C                             |
| ETIM Class                       | EC002892                                |
| Warranty                         | 5 years                                 |

#### OPTICAL DATA

|                                 |               |
|---------------------------------|---------------|
| Fixture luminous flux (lm)      | 18745         |
| Luminaire efficacy (lm/W)       | 122           |
| Colour temperature (K)          | 4000          |
| Colour Code                     | 940           |
| Light colour                    | Neutral White |
| CRI (Ra)                        | 90            |
| Colour Variation Initial (SDCM) | 3             |
| Distribution type               | Symmetric     |
| Glare control                   | < 22          |
| Photobiological Risk Group      | RG0           |

#### ELECTRICAL DATA

|                             |       |
|-----------------------------|-------|
| Total power consumption (W) | 153.6 |
| Current (A)                 | 450   |

# Concord

## COLOSSAL 1200mm 940 OPAL DIR WHITE DALI 2071297

|                                                                       |                                |
|-----------------------------------------------------------------------|--------------------------------|
| Mains voltage (V)                                                     | 220-240V                       |
| Lamp power factor                                                     | 0.95                           |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x % | 10                             |
| Electrical protection                                                 | Class I                        |
| Control gear required                                                 | No                             |
| Control gear type                                                     | LED driver constant current    |
| Transformer required                                                  | No                             |
| Dimmable                                                              | Yes                            |
| Dimming method                                                        | DALI                           |
| Drive current (mA)                                                    | 450                            |
| Inrush Current (A)                                                    | 25                             |
| Inrush Duration ( $\mu$ s)                                            | 280                            |
| Glow Wire Test ( $^{\circ}$ C)                                        | 650                            |
| Energy Efficiency Class (A->G) of contained light source              | C, C(more than 1 Light Source) |
| Nominal Frequency (Hz)                                                | 50/60Hz                        |
| LED Flickering Rate                                                   | Ultra low (5% or less)         |
| Max. Luminaires per 10A C Breaker                                     | 24                             |
| Max. Luminaires per 13A C Breaker                                     | 31                             |
| Max. Luminaires per 16A C Breaker                                     | 40                             |
| Max. Luminaires per 20A C Breaker                                     | 49                             |
| Max. Luminaires per 10A B Breaker                                     | 13                             |
| Max. Luminaires per 16A B Breaker                                     | 24                             |
| Max. Luminaires per 20A B Breaker                                     | 30                             |

### LIFETIME DATA

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 170000 |
| Lifespan L80 B20 | 145000 |
| Lifespan L90 B10 | 66000  |

### PHYSICAL DATA

|                |                                  |
|----------------|----------------------------------|
| Housing colour | RAL 9016 - Traffic white / Bezel |
| IP rating      | IP40/20                          |

# Concord

## COLOSSAL 1200mm 940 OPAL DIR WHITE DALI 2071297

|                               |                  |
|-------------------------------|------------------|
| IK rating                     | IK07             |
| Diffuser finish               | Opal             |
| Diffuser material             | PC Polycarbonate |
| Nominal Product Height (mm)   | 93               |
| Nominal Product Diameter (mm) | 1168             |
| Weight (kg)                   | 23.0             |

### PACKAGING

|                                       |                |
|---------------------------------------|----------------|
| Single packaging type                 | Carton         |
| Product EAN number                    | 5025768712977  |
| Packaging single length / height (cm) | 14.0           |
| Packaging single width (cm)           | 123.0          |
| Packaging single depth (cm)           | 123.0          |
| DUN14 (outer)                         | 05025768712977 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 14.0           |
| Packaging outer width (cm)            | 123.0          |
| Packaging outer depth (cm)            | 123.0          |

### SAFETY DATA

|                                     |      |
|-------------------------------------|------|
| Optimal operating condition (°C)    | 5-25 |
| Special purpose lamp                | No   |
| Dry applications use only           | No   |
| Suitable for household illumination | No   |