



Features

- Concord OFFICELYTE 600X600 HO 4K EM is a high performance low glare luminaire for offices and education applications. Ceiling recessed 600x600mm. Micro Prismatic optics. White RAL 9010. Constant current driver. 3 hours emergency operation with integral batteries. 4000K Neutral White LED, Typical CRI=85, chromaticity tolerance of 3-step MacAdam ellipse, lumen package of 4,350lm, total power consumption 35W, efficacy of 124lm/W. Lifespan 120,000 hours L70B50, 58,000 hours L80B20, UGR<19. IK02, IP20, Electrical Protection Class I, Photobiological Risk Group 1. PMMA diffuser, Glow Wire test 650°C.

Product Overview

Product name	OFFICELYTE 600X600 HO 4K EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Office, Hospitality, Retail, Education
ETIM Class	EC002892
Fixture luminous flux (lm)	4350
Luminous flux (lm)	4350
Luminaire efficacy (lm/W)	124
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	233

OFFICELYTE 600X600 HO 4K EM 2069258

Total power consumption (W)	35
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Remote
Dimmable	No
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK02
Product EAN number	5025768692583
Warranty	5 years
Dimming method	N/A

Data table

GENERAL DATA

Product name	OFFICELYTE 600X600 HO 4K EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Office, Hospitality, Retail, Education
Performance ambient temperature T _q (°C)	25
ETIM Class	EC002892
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	4350
Luminous flux (lm)	4350
Luminaire efficacy (lm/W)	124
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White

OFFICELYTE 600X600 HO 4K EM 2069258

CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	233
Emergency duration (h)	3

ELECTRICAL DATA

Total power consumption (W)	35
Mains voltage (V)	230-240V
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	Yes
Control gear type	Electronic ballast
Control gear mounting	Remote
Dimmable	No
Dimming method	N/A
Drive current (mA)	850
Inrush Current (A)	24.7
Inrush Duration (µs)	268
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	18
Max. Luminaires per 13A C Breaker	23
Max. Luminaires per 16A C Breaker	28
Max. Luminaires per 20A C Breaker	35
Max. Luminaires per 10A B Breaker	11
Max. Luminaires per 13A B Breaker	14
Max. Luminaires per 16A B Breaker	17
Max. Luminaires per 20A B Breaker	21

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L80 B20	58000

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK02
Diffuser finish	Matt/satinized
Diffuser material	PMMA Acrylic
Nominal Product Length (mm)	595
Nominal Product Width (mm)	595
Nominal Product Height (mm)	87
Cutout Dimensions (W x L in mm or Diameter in mm)	575 x 575
Weight (kg)	7.1
Recessed Depth (mm)	200

PACKAGING

Single packaging type	Carton
Product EAN number	5025768692583
Packaging single length / height (cm)	63.5
Packaging single width (cm)	73.0
Packaging single depth (cm)	15.5
DUN14 (outer)	05025768692583
Units per outer package	1
Packaging outer length / height (cm)	63.5
Packaging outer width (cm)	73.0
Packaging outer depth (cm)	15.5

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No

Concord

OFFICELYTE 600X600 HO 4K EM
2069258

Suitable for household illumination

No