

INSAVER 150 HE TOPPER LED NW PIR PLUS3
3033925



Features

- InsaVER HE Topper is a ceiling recessed LED downlight with integrated PIR sensor with time (up to 8 mins) and daylight lux level settings. Die-cast aluminium body, Non dimmable LED driver, 8W, 800lm, 100lm/W, 4000K, shallow recessed depth of 55mm. Wieland GST compatible

Product Overview

Product name	INSAVER 150 HE TOPPER LED NW PIR PLUS3
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	External
General application	Hospitality, Logistics & Industry, Office
ETIM Class	EC001744
Fixture luminous flux (lm)	800
Luminaire efficacy (lm/W)	100
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Beam Angle (°)	64
Total power consumption (W)	8
Electrical protection	Class II
Control gear type	Electronic ballast
Housing colour	White
IP rating	IP44/20
IK rating	IK02
Product EAN number	8711971339250
Warranty	3 years

INSAVER 150 HE TOPPER LED NW PIR PLUS3 3033925

Dimming method	N/A
----------------	-----

Data table

GENERAL DATA

Product name	INSAVER 150 HE TOPPER LED NW PIR PLUS3
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	External
General application	Hospitality, Logistics & Industry, Office
ETIM Class	EC001744
Warranty	3 years

OPTICAL DATA

Fixture luminous flux (lm)	800
Luminaire efficacy (lm/W)	100
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Adjustable chromaticity	N
Beam Angle (°)	64

ELECTRICAL DATA

Total power consumption (W)	8
Mains voltage (V)	220-240V
Electrical protection	Class II
Control gear required	No
Control gear type	Electronic ballast
Transformer required	Yes
Dimming method	N/A
Drive current (mA)	350
Glow Wire Test (°C)	650

INSAVER 150 HE TOPPER LED NW PIR PLUS3 3033925

Energy Efficiency Class (A->G) of contained light source	E
---	---

PHYSICAL DATA

Housing colour	White
IP rating	IP44/20
IK rating	IK02
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Reflector finish	Other
Nominal Product Height (mm)	55
Nominal Product Diameter (mm)	165
Cutout Dimensions (W x L in mm or Diameter in mm)	145 x 145
Weight (kg)	0.7

PACKAGING

Single packaging type	Carton
Product EAN number	8711971339250
Packaging single length / height (cm)	25.0
Packaging single width (cm)	17.0
Packaging single depth (cm)	14.0
DUN14 (outer)	18711971339257
Units per outer package	12
Packaging outer length / height (cm)	78.0
Packaging outer width (cm)	36.0
Packaging outer depth (cm)	31.0

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No