

OBICO 80 IP65 820LM 2CCT 930/940 DIM WHT 0005366



Features

- Integrated LED recessed spotlight, 2-axis adjustable (horizontal rotation 360°, vertical tilt 30°) RAL9016 white bezel colour, two temperature light colors selectable: 3000K, 4000K. Lumen output 820lm (4000K), 8.2W, dimmable trailing/leading edge, 38° degree beam angle, aluminium and steel body, low profile 40mm recessed depth, IP65 frontal degree, IK03, loop-in/loop-out terminals for fast wiring, 80mm cutout, clear lens. Air-proof, to limit air leakage when used in residential applications within the building's thermal envelope. Directly coverable with insulation material according to EN60598-1

Product Overview

Product name	OBICO 80 IP65 820LM 2CCT 930/940 DIM WHT
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Residential & Consumer, Retail
ETIM Class	EC001744
E-number FI	4278508
Fixture luminous flux (lm)	820
Luminaire efficacy (lm/W)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	4
Beam Angle (°)	38
Photobiological Risk Group	RG1
Total power consumption (W)	8.2
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	RAL9016



OBICO 80 IP65 820LM 2CCT 930/940 DIM WHT
0005366

IP rating	IP65/20
IK rating	IK03
Product EAN number	5410288053660
Warranty	5 years
Dimming method	Mains: leading / trailing edge