

## START ECO SPOT 480lm 840 IP44 WHT **0005371**



## **Features**

• Integrated LED recessed spotlight, vertical tilt 30°, 480lm, 5.0W, non-dimmable, 4000K, 38° degree beam angle, polycarbonate white body, low profile 47mm recessed depth, IP44 from the front, IK03, loop-in/loop-out terminals for fast wiring, 86mm bezel diameter, 68-74mm cutout, clear lens. Additional silver bezel included in the packaging.

## **Product Overview**

Product name	START ECO SPOT 480lm 840 IP44 WHT
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4278143
Fixture luminous flux (lm)	480
Luminaire efficacy (lm/W)	96
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	38
Photobiological Risk Group	RG0
Total power consumption (W)	5
Electrical protection	Class II
Dimmable	No
Minimum dimming level (%)	10
LED Flickering Rate	Medium (21% - 40%)
Housing colour	White
IP rating	IP44/20



## START ECO SPOT 480lm 840 IP44 WHT **0005371**

IK rating	IK03
Product EAN number	5410288053714
Warranty	3 years
Colour Code	840
Dimming method	N/A