

Resisto GRP 1500 IP66 7000lm 840 0010317



Features

- Resisto GRP, integrated LED weatherproof luminaire, with smooth body finish optimized for LEDs with flat diffuser, easy to handle. Stainless steel diffuser clips and fixing brackets for surface mounting. The luminaire benefits from a water and dust resistant GRP body and PMMA diffuser. 7000lm; 51W; 137lm/W; 4000K; SDCM<4; non dimmable; CRI80; IP66; IK02; Class I; 72,000hrs (L80B20) lifespan; 1454mm x 90mm x 120mm; D-mark.

Product Overview

Product name	Resisto GRP 1500 IP66 7000lm 840
Technology	LED
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4357082
Fixture luminous flux (lm)	7000
Luminaire efficacy (lm/W)	137
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	4
Beam Angle (°)	120
Photobiological Risk Group	RG1
Total power consumption (W)	51
Electrical protection	Class I
Dimmable	No
Housing colour	Grey
IP rating	IP66
IK rating	IK02
Product EAN number	5410288103174
Warranty	5 years
Dimming method	N/A

SYLVANIA

Resisto GRP 1500 IP66 7000lm 840
0010317

Light your world