

Resisto 1500 IP66 8500lm 865 0010248



Features

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 8500lm; 61W; 139lm/W; 6500K; SDCM<5; non dimmable; CRI80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 1500mm x 89mm x 88mm; D-mark.

Product Overview

Product name	Resisto 1500 IP66 8500lm 865
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4357061
Fixture luminous flux (lm)	8500
Luminaire efficacy (lm/W)	139
Colour temperature (K)	6500
CRI (Ra)	80
Colour Consistency (SDCM)	5
Colour Variation Initial (SDCM)	5
Beam Angle (°)	110
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	61
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)



Resisto 1500 IP66 8500lm 865
0010248

Housing colour	Grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288102481
Warranty	5 years
Dimming method	N/A