

Resisto 1200 IP65 2800lm 840 SSA  
0010230



Features

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 2800lm; 20W; 140lm/W; 4000K; SDCM<5; CRI80; IP66; IK08 (sensor IK03); Class I; 69,000hrs (L80B20) lifespan; 1288mm x 87mm x 80mm; D-mark; SylSmart Connected Building enabled.

Product Overview

|                                 |                                                           |
|---------------------------------|-----------------------------------------------------------|
| Product name                    | Resisto 1200 IP65 2800lm 840 SSA                          |
| Technology                      | LED                                                       |
| Cap/Base                        | N/A                                                       |
| Housing                         | PC Polycarbonate                                          |
| Mount                           | Ceiling surface mounting, Suspended, Wall surface mounted |
| General application             | Logistics & Industry                                      |
| ETIM Class                      | EC002892                                                  |
| Fixture luminous flux (lm)      | 2800                                                      |
| Luminaire efficacy (lm/W)       | 140                                                       |
| Colour temperature (K)          | 4000                                                      |
| Light colour                    | Neutral White                                             |
| CRI (Ra)                        | 80                                                        |
| Colour Consistency (SDCM)       | 5                                                         |
| Colour Variation Initial (SDCM) | 5                                                         |
| Beam Angle (°)                  | 110                                                       |
| Glare control                   | < 22                                                      |
| Photobiological Risk Group      | RG1                                                       |
| Total power consumption (W)     | 20                                                        |
| Electrical protection           | Class I                                                   |
| Control gear type               | LED driver constant current                               |
| Dimmable                        | Yes                                                       |



Resisto 1200 IP65 2800lm 840 SSA  
0010230

|                           |                        |
|---------------------------|------------------------|
| Minimum dimming level (%) | 1                      |
| LED Flickering Rate       | Ultra low (5% or less) |
| Housing colour            | Grey                   |
| IP rating                 | IP65                   |
| IK rating                 | IK08                   |
| Product EAN number        | 5410288102306          |
| Warranty                  | 5 years                |
| Dimming method            | SylSmart SSA           |