

## OptiClip 1200 3000K C8 WH SSC WHITE 0044014



### Features

• OPTICLIP 1200 3000K C8 WH SSC WHITE is a high efficacy low glare luminaire with replaceable light engines for office and education applications. Ceiling recessed LED luminaire with white colour plastic optic, direct light distribution, luminaire dimensions: 1195x295x20mm, Sylvania White body colour (RAL9016), IP40 (from the front), IK07, SylSmart Standalone capable, low LED flicker (+/-5%), Warm White (3000K) LED Colour Temperature, 3100lm luminous flux, 26W power consumption, 119lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<19, Luminance at 65° < 2000 cd/m<sup>2</sup>, lifespan: 62,000 hours L80B20, photobiological safety risk group 1. Electrical protection Class II. Glow wire test 850°C.

### Product Overview

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Product name                    | OptiClip 1200 3000K C8 WH SSC WHITE |
| Technology                      | LED (3 SDCM)                        |
| Cap/Base                        | N/A                                 |
| Housing                         | Steel                               |
| Mount                           | Ceiling recessed mounting           |
| Fixture rating                  | Enclosed                            |
| General application             | Education, Office                   |
| ETIM Class                      | EC002892                            |
| Fixture luminous flux (lm)      | 3100                                |
| Luminaire efficacy (lm/W)       | 119                                 |
| Colour temperature (K)          | 3000                                |
| Light colour                    | Warm White                          |
| CRI (Ra)                        | 80                                  |
| Colour Variation Initial (SDCM) | 3                                   |
| Beam Angle (°)                  | 80                                  |
| Glare control                   | < 19                                |
| Photobiological Risk Group      | RG1                                 |
| Total power consumption (W)     | 26                                  |

## OptiClip 1200 3000K C8 WH SSC WHITE 0044014

|                           |                                  |
|---------------------------|----------------------------------|
| Electrical protection     | Class II                         |
| Control gear type         | LED driver constant current      |
| Dimmable                  | Yes                              |
| Minimum dimming level (%) | 1                                |
| LED Flickering Rate       | Ultra low (5% or less)           |
| Housing colour            | RAL 9016 - Traffic white / Bezel |
| IP rating                 | IP40/20                          |
| IK rating                 | IK07                             |
| Product EAN number        | 5410288440149                    |
| Warranty                  | 5 years                          |
| Dimming method            | SylSmart SSC                     |