

## START DOWNLIGHT 205 IP44 SSC01 2025LM 840 0030376



### Features

- Ceiling recessed LED downlight IP44 (from the front), with only 60mm product depth and 205mm cutout. Ideal replacement for 1x42W CFL downlights. The polycarbonate diffuser allows for a wider light distribution and increased spacings between luminaires. Die-cast aluminium body, 2025LM, 20W, 101lm/W, 4000K, Driver Current: 600mA, CRI80, 74° beam angle, IP44 from the front, IK07, (HxW) 60x205mm, Class 2, 220-240V, SylSmart Standalone Scene enabled . Meets TP(a) requirements.

### Product Overview

|                                 |                                           |
|---------------------------------|-------------------------------------------|
| Product name                    | START DOWNLIGHT 205 IP44 SSC01 2025LM 840 |
| Technology                      | LED                                       |
| Cap/Base                        | N/A                                       |
| Housing                         | Aluminium                                 |
| Mount                           | Ceiling recessed mounting                 |
| General application             | Hospitality, Retail                       |
| ETIM Class                      | EC001744                                  |
| Fixture luminous flux (lm)      | 2025                                      |
| Luminous flux (lm)              | 2025                                      |
| Luminaire efficacy (lm/W)       | 101                                       |
| LOR (%)                         | 100                                       |
| Colour temperature (K)          | 4000                                      |
| Light colour                    | Neutral White                             |
| CRI (Ra)                        | 80                                        |
| Colour Variation Initial (SDCM) | 5                                         |
| Beam Angle (°)                  | 74                                        |
| Glare control                   | < 25                                      |
| Photobiological Risk Group      | RG0                                       |
| Total power consumption (W)     | 20                                        |
| Electrical protection           | Class II                                  |
| Control gear type               | Electronic ballast                        |
| Dimmable                        | Yes                                       |



START DOWNLIGHT 205 IP44 SSC01 2025LM 840  
0030376

|                     |                         |
|---------------------|-------------------------|
| LED Flickering Rate | Ultra low (5% or less)  |
| Housing colour      | RAL 9003 - Signal white |
| IP rating           | IP44/20                 |
| IK rating           | IK07                    |
| Product EAN number  | 5410288303765           |
| Warranty            | 5 years                 |
| Dimming method      | SylSmart SSC            |