



Features

- LED batten, T8 replacement, ease of installation through 2 part push-in design of the housing (safety cable included), through wiring capability, steel housing, 1100lm, 9W, 122lm/W, 3000K, CRI80, 3 step MacAdam ellipse, symmetric wide beam angle, Class I, 90000 hrs L80B20 lifespan, non-dimmable driver, IK08, IP20, 672 x 70 x 76.5mm (LxWxD) dimensions, 0.8kg weight.


Product Overview

Product name	Wayline 600 1100lm 830
Technology	LED
Housing	Steel
General application	Logistics & Industry
ETIM Class	EC000109
E-number FI	4278297
Fixture luminous flux (lm)	1100
Luminaire efficacy (lm/W)	122
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	115
Photobiological Risk Group	RG1
Total power consumption (W)	9
Electrical protection	Class I
Dimmable	No
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK08
Product EAN number	5410288489162

Wayline 600 1100lm 830
0048916

Warranty	5 years
Dimming method	N/A

Photometry



Technical drawings

