



### Features

- LED batten, T8 replacement, ease of installation through 2 part push-in design of the housing (safety cable included), through wiring capability (TP3 = 3 core), sheet steel, 2812LM, 26W, 108lm/W, 4000K, drive current: 350mA, CRI 80, 138° wide beam angle, electronic driver (non dimmable), IP20, IK07, 50,000 hrs (L70), (LxWxH) 1205x66x76mm, 5 step MacAdam ellipse, 3kg, white RAL9016, Class 1, 220-240V, energy class: A++, A+, A.


### Product Overview

Product name	SYLBATTEN LED 1205MM 3000LM 4000K EB (TP3)
Technology	LED
Housing	Steel
Mount	Ceiling surface mounting
Fixture rating	Enclosed
Environment	Internal
General application	Logistics & Industry
ETIM Class	EC000109
E-number FI	4274239
E-number SE	7213390
Fixture luminous flux (lm)	2812
Luminaire efficacy (lm/W)	108.15
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	5
Colour Variation Initial (SDCM)	5
Beam Angle (°)	138
Glare control	< 29
Photobiological Risk Group	RG0

## SYLBATTEN LED 1205MM 3000LM 4000K EB (TP3) 0045172

Total power consumption (W)	26
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Built-in
Dimmable	No
LED Flickering Rate	Medium (21% - 40%)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288451725
Warranty	5 years
Dimming method	N/A

### Photometry



### Technical drawings



Version	L	H	W
600mm	605	76	66
1200mm	1205	76	66
1500mm	1505	76	66
1200mm PIR	1305	76	66
1500mm PIR	1605	76	66